


WIRE NUTS

STANDARD TWIST-ON CONNECTORS

ADI PRO

Use ADI PRO Wire Nuts to fasten two or more low-voltage electrical conductors in commercial and residential applications. Tapered coil metal inserts thread onto the wires and hold them securely, while color coded plastic caps insulate and protect.



FEATURES

Tough Thermoplastic

UL 94V-2 Flame Retardant Shell Rated for 221°F (105°C)

Zinc Plated Square Wire Spring

For Use With Stranded or Solid Cable

Product Specifications

PART #	Dimensions	Color
0E-WNGY Wire Range: 300 V Max. 22-14 AWG Max. 1 #16 w/ 1 #18 w/ 1 #20. Min. 2 #22	A. 0.15 B. 0.256 C. 0.339 D. 0.217 E. 0.598	Gray
0E-WNBL Wire Range: 300 V Max. 22-14 AWG Max. 3 # 16. Min. 2 # 22	A. 0.161 B. 0.28 C. 0.39 D. 0.217 E. 0.697	Blue
0E-WNOR Wire Range: 300V/600V Max. 22-14 AWG Max. 4 #16 w/1 #20 Min. 1#18 w/1#20	A. 0.197 B. 0.382 C. 0.5 D. 0.268 E. 0.866	Orange
0E-WNYW Wire Range: 300V/600V Max. 22-10 AWG Max. 2 #22 w/ 2 #14 Min. 3 #20	A. 0.236 B. 0.433 C. 0.551 D. 0.268 E. 0.969	Yellow



For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands