

Technical Specifications

VIP-893/VIP-893S IP Interactive Console

- Desktop interactive IP device with 10.1" color touch screen display, loudspeaker, USB handset, and cradle attachment
- Sends pre-recorded audio files at the push of a button
- Sends microphone pages, either "Live" or Record & Send for feedback elimination
- Sends text messages to Valcom LED signs
- Makes/receives bidirectional voice calls to Valcom and SIP endpoints
- Receives audio pages
- Up to 10 schedules and 100 events can be defined (VIP-893S)
- Simple configuration via web browser interface
- Adjustable display tilt



Send live or pre-recorded audio and text with the push of a button.

Description:

Valcom's VIP-893 Interactive Console is a touchscreen device designed to broadcast daily communications within a small to mid-size organization. The versatility of the Interactive Console makes daily announcements less taxing and more efficient for individuals who relay the information your organization needs. With one touch of a button announcements from pre-loaded audio and text files are sent to multiple endpoints including speakers, horns, desktop alerts and LED signs throughout your organization. The Interactive console doesn't take away the ability to send live voice announcements as you still have the capability to do messages on the fly as needed. One the most important aspect of the Interactive Console is how quickly you can initiate emergency alerts and relay important information to multiple departments across your organization. One push of a button sends multiple messages to multiple locations.

2024 Rev.1.2.14

Technical Specifications

SPECIFICATIONS

NOMINAL POWER REQUIREMENTS

Power over Ethernet Plus (PoE+): IEEE 802.3af compliant switch or injector

External via rear panel barrel connector:

Voltage: 12 Vdc

Current: 2 Amp power supply included

ETHERNET CONNECTION

A 10ft Ethernet cable

ACCESS METHODS

Touchscreen activation of announcements

Remote access activation via Web browser

SIP protocol phone calls

Valcom intercom and page group calls

MOUNTING

Table Mounting: 4 non-skid pads protects the table surface and provides slip resistance

ENVIRONMENT

Temperature: +32 to +104 °F (0 to +40 °C)

Humidity: 0-85% non-precipitating

DIMENSIONS AND WEIGHT

12.00in W x 8.00in H x 7.50in D

(30.50cm x 20.30cm x 19.10cm)

Weight: 3.80lbs (1.70kg)

Shipping Weight: 7.40lbs (4.05kg)

ARCHITECTS AND ENGINEERS

The Interactive Console Desktop Display, model VIP-893/VIP-893S, shall consist of a 10.10in color touch screen display, a loudspeaker, a USB handset and a cradle attachment.

THE VIP-893/VIP-893S Interactive Console Desktop Display shall send live or pre-recorded audio files at the push of a button. The P Interactive Console can receive and play broadcast paging announcements from other IP Valcom FXO, FXS, or SIP gateways.

The VIP-893/VIP-893S Interactive Console Desktop device shall enable voice announcements live or pre-recorded to Valcom IP audio gateways, IP speakers/horns, and IP speakers with text. The VIP-893/VIP-893S shall enable pre-defined text messages to be sent simultaneously with the recorded audio to endpoints that support both. The VIP-893/VIP-893S shall initiate and receive intercom calls via the built-in microphone or handset from Valcom IP and SIP endpoints.

The VIP-893S shall include basic scheduling functions to send recorded announcements and/or text messages to Valcom IP endpoints.

The VIP-893/VIP-893S Interactive Console Desktop Display shall be a simple configuration via web browser interface. The VIP-

893/VIP-893S shall be powered via an Power over Ethernet Plus (PoE+): IEEE 802.3af compliant switch or injector. A 10ft Ethernet cable is pre-connected at the factory, for connecting directly to an Ethernet switch.

Setup of the VIP-893/VIP-893S Interactive Console Desktop Display will be performed using the Valcom IP Solutions Setup Tool. Additional programming will be done directly in the VIP-893/VIP-893S through the touch screen interface, and via web browser interface.

The VIP-893/VIP-893S Interactive Console Desktop Display shall be constructed with a pre-installed handset and an adjustable tilt screen for glare reduction. The VIP-893/VIP-893S shall be table mountable with 4 non-skid pads to protect the table surface and to provide slip resistance. The VIP-893/VIP-893S is suitable for indoor use.

Maximum dimensions shall be: 12.00in W x 8.00in H x 7.50in D (30.5cm x 20.30cm x 19.10cm). Weight shall be approximately: 3.80lbs (1.70kg).

Warranty information may be found on our website at www.valcom.com/warranty.