

DOOR ENTRY SYSTEMS

POWER SUPPLIES AND ACCESSORIES



1998NA

AUDIO PORTER SWITCHBOARD. S1





Audio porter switchboard in desk version for Simplebus 1 system with microswitch keypad and 32-character alphanumeric display. Ergonomic handset with easier hangup, thanks to concealed magnetic panels. Allows the code and name of the called and calling users to be displayed, keeping unanswered calls stored in the memory. Manages Day/Night mode and user/user intercom service. Allows management of alarm indications originating from users. Up to 1000 users can be saved. Supplied with a removable cable with connection hub. 24 VAC power supply with art. 1195. Dimensions (L x H x D): $225 \times 100 \times 225 \text{ mm}$.



DOOR ENTRY SYSTEMS

POWER SUPPLIES AND ACCESSORIES



1998NA

AUDIO PORTER SWITCHBOARD. S1			
COMPATIBLE SYSTEMS			
Audio/video Simplebus 1	Yes		
Audio Simplebus 1	Yes		
DISPLAY			
Display type	32-character alphanumerical display		
AUDIO FEATURES			
Technologies implemented	Full-Duplex		
ELECTRICAL CHARACTERISTICS			
Max/min absorption (mA)	20 ÷ 200		
Type of power supply	External power supply		
НА	HARDWARE FEATURES		
Visual signalling	Yes		
Number of push-buttons (n°)			
	36		
Acoustic signalling	Yes		
Acoustic signalling Number of outputs (n°)	Yes		
Acoustic signalling Number of outputs (n°)	Yes 2		
Acoustic signalling Number of outputs (n°) ENVIRONMENT	Yes 2 TAL AND COMPLIANCE FEATURES		
Acoustic signalling Number of outputs (n°) ENVIRONMENT	Yes 2 AL AND COMPLIANCE FEATURES I (B1)		
Acoustic signalling Number of outputs (n°) ENVIRONMENT Environmental class Door opener	Yes 2 TAL AND COMPLIANCE FEATURES I (B1) MAIN FUNCTIONS		

CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Type of buttons	Mechanical

The technical specifications are subject to change without prior notice.



DOOR ENTRY SYSTEMS

POWER SUPPLIES AND ACCESSORIES



1998NA

AUDIO PORTER SWITCHBOARD. S1

	MAIN FEATURES
Height (inch) (in)	3.54
Depth (inch) (in)	9.06
Product weight (oz) (oz)	52.91
Operating temperature (°F)	23 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 90
Supply voltage	24 VDC
Maximum current absorption (mA)	200

SOFTWARE/FIRMWARE SPECIFICATIONS

No. of storable users (n°)

1000

	GENERAL DATA
Type of finishing materials	ABS

FUNCTIONS	
Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes

	COMPATIBILITY
Simplebus 1 audio system	Yes
	CONNECTIVITY
RS232 ports (n°)	1