

**QUAM COMPONENTS** 

QC10W is a UL Listed, single-gang, 20W, ten-step, continuous rotary, audio level attenuator with an OFF position. It has a white powder coated faceplate with a white knob.



APPLICATION	Intended Use: Primary Use:	Indoor environment Attenuates audio power to any number of loudspeakers up to 20W load For use with 25V or 70V distributed audio systems
	Installation:	Single-gang electrical box, 2 1/8" deep
AUDIO	Power Rating:	20W Continuous
PERFORMANCE	Attenuation (Ref:25V, 70.7V line):	Position 10 : Full Signal
		Position 9-3:-3dB Each
		Position 2-1:-6dB Each
		Position 0 : No Signal
	Insertion Loss:	< 0.5dB
	Frequency Response:	65Hz - 17kHz, EIA 426A Standard
	Audio Connection:	10", Color-coded, Pre-tinned Leads
COMPONENT	Dimension:	4 % <sub>16</sub> " (H) x 2 <sup>13</sup> / <sub>16</sub> " (W) x 2 <sup>1</sup> / <sub>4</sub> " (D)
	Weight:	1 lbs.
	Faceplate:	White powder coated steel
	Other:	White knob
CERTIFICATIONS	UL Listed 813	When installed in accordance with supplied instructions and connected to supply circuits in accordance with ANSI/NFPA70, NEC, and AHJ
RECOMMENDED	Enclosures:	Surafce Mount — SE4W







