

Quam SYSTEM 17/8

SYSTEM 17/8 is a complete, UL Listed, shallow depth, lightweight, 2' x 2' ceiling tile replacement loudspeaker system consisting of an 8" O.D., foam edge loudspeaker with a 10 oz. magnet and an 8 Ohm impedance. The molded fiber enclosure is 1,283 CID. The SYSTEM 17/8 has a powder coated steel baffle with standard perforation and four (4) seismic tie-off points. The cable clamp is included. No assembly required.



APPLICATION	Intended Use: Program Material: Installation: City of Chicago Approved:	Indoor environment Signal tones, voice, and music Mounted parallel to floor plane in a 24" wide suspended ceiling tile grid Material and construction permits use where ceiling plenum is part of the air handling system
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Maximum Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	95dB SPL, 1W/1M 20W RMS, EIA 426A Standard 20W @ 8 Ohms 102dB SPL, 5W/1M BeFe Ceramic, 10 oz. Nominal 60Hz - 17kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half Space 3 ½", Color-coded, Pre-tinned Leads
COMPONENT	Dimension: Weight: Loudspeaker Model: Loudspeaker Specs: Integral Enclosure: Grille: Finish:	3 ½" (H) x 23 13/16" (W) x 23 13/16" (D) 6.36 lbs. 8C10FEPAX 8" O.D. loudspeaker, 5 oz. magnet 1,283 CID molded fiber Standard perforated steel with four (4) seismic tie-off points White powder coat finish
CERTIFICATION	UL Listed 1480 UL Listed 2043	When installed with supplied installation instructions and requirements of NEC /AHJ. (UEAY, UEAY7- Canada) Suitable for use in air-handling spaces

