



Model No.

SLS

Rackmount Shelf with Stay-open Latch

| | |
|-----------------|-------------------------------|
| Overall Height: | 2.5" [64] |
| Rack Space: | Slightly more than 1U |
| Overall Depth: | 14.625" [371] |
| Max. Extension: | 14.0" maximum shelf extension |
| Overall Width: | 19.0" [483] |
| Shelf Width: | 17.5" [445] |
| Load Capacity: | 50 lbs. [23 kg] |



RACKMOUNT SHELF slides out and latches securely in the open position to stay in place while you work, then latches in the closed position when finished. Ideal for holding a laptop or tablet while working on rackmounted equipment.

FEATURES

HOW TO MOUNT: Four-point mounting is required. Install the shelf on the cabinet's front mounting rails. Two sets of brackets are provided to accommodate variations for rear-mount support:

- **Mounting shelf in wood cabinet without rear rails:** The shelf has two factory-mounted brackets in the rear. Loosen the wing nuts to extend the brackets to touch the inside of the cabinet (maximum extension width 26.5-inches). See install sheet for instructions on drilling holes to match those in brackets.
- **Mounting the shelf in a cabinet with rear rails:** Use the side brackets (included), aligning holes with matching tapped holes in rear rails. Loosen wing nuts on the rear brackets and extend them to touch the side brackets, aligning holes and securing with included hardware. Minimum rear support extension is 14.88-inches; maximum extension is 23.5-inches. See install sheet for complete instructions.

MATERIAL: 16-gauge certified U.S. steel

FINISH: Smooth black powder epoxy finish

FRONT: Center latch turns to loosen or secure shelf in place.

REAR: Factory-mounted rear brackets with wing nuts.

CABLE MANAGEMENT: Rear lacing points

HARDWARE BAG: Side brackets, screws

A&E SPECIFICATIONS

The 19-inch rackmount shelf shall be Lowell model SLS, which shall be 16-gauge certified U.S. steel construction with smooth black powder epoxy finish. The shelf shall be capable of sliding forward and latching in place in the open position. It shall require four-point mounting and include brackets to accommodate two mounting applications: two factory-mounted rear brackets shall be capable of extending to mount directly to the sides of a wood cabinet (maximum width 26-1/2 in.); a separate pair of side brackets shall be included in the hardware bag to mount to the shelf's rear brackets and a cabinet's rear rails. Overall shelf dimensions shall be 2.5-in. high x 19-in. wide x 14.88-in. deep. Load capacity shall be 50 lbs. The shelf shall be made in the U.S.A.

TECHNICAL DRAWINGS

Dimensions are inches and [mm] unless stated otherwise.

