USB-C to RJ45 Serial Rollover Cable (M/M) - Cisco Compatible, 250 Kbps, 6 ft. (1.8 m)

MODEL NUMBER: **U209-006-RJ45XC**

Highlights

- Supports data transfer rates up to 250 Kbps
- Supports remote wake-up and power management
- Premium double-shielded cable eliminates crosstalk and reduces EMI/RFI interference
- Compatible with Windows, macOS and Linux operating systems
- Designed for Cisco equipment with no adapters or external power required

System Requirements

- Computer with USB-C port and Windows, macOS or Linux operating system
- Cisco device with RJ45 console port

Package Includes

- U209-006-RJ45XC USB-C to RJ45 Serial Rollover Cable, M/M, 6 ft. (1.8 m)
- Owner's manual

Connects your computer or laptop's USB-C port to a Cisco modem, router, firewall, switch or other serial-based Cisco device with an RJ45 console port.

Features

Connects Your Computer's USB-C Port to a Cisco Device
Directly connect the RJ45 console port on your Cisco modem, router, firewall, switch or other serial-based Cisco device to the USB-C port on your computer or laptop. The U209-006-RJ45XC supports data transfer rates up to 250 Kbps, as well as remote wake-up and power management. It is compatible with Windows, macOS and Linux.

Filtering EMI/RFI Line Noise Helps Your Equipment Perform Better
This Cisco-compatible cable blocks disruptive EMI (electromagnetic interference) and RFI (radio frequency interference) line noise that can disturb your network equipment and inflict hardware damage or data loss. Premium double-shielding eliminates crosstalk and helps your connected components perform better and last longer.

Specifically Designed for Cisco Equipment
The serial cable is compatible with both older and current Cisco models. It requires no external power or additional adapters. You may download and install the necessary driver from the product page at tripplite.eaton.com/support (see the included owner's manual for directions).

Specifications

OVERVIEW	
UPC Code	037332268655
Technology	Serial; USB

POWER	
USB Power Delivery (PD) Charging Support	No

PHYSICAL	
Color	Black
Cable Jacket Color	Blue
Connector Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	RJ45: 5.5MM; USB: 4.7MM
Cable Length (ft.)	6
Cable Length (m)	1.83
Cable Length (in.)	72
Unit Packaging Type	Box
Unit Weight (lbs.)	0.2425
Unit Weight (kg)	0.11

ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-4° to 140°F (-20° to 60°C)
Operating Humidity Range	0% TO 90% RH, NON-CONDENSING
Storage Humidity Range	0% TO 90% RH, NON-CONDENSING

COMMUNICATIONS	
Network Compatibility	250 Kbps

CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	RJ45 (MALE)

FEATURES & SPECIFICATIONS	
IP68 Rated	No
IP20 Rated	No
Remote Wakeup Support	Yes
Driver Required	Yes

STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)

WARRANTY & SUPPORT	

TRIPP·LITE
by **E·T·N**

Product Warranty Period (Worldwide)	3-year limited warranty

TRIPP·LITE
by **E·T·N**