

Product data sheet

Specifications



APC DIN Rail - Panel Mount UPS with Standard Battery 500VA 120V

SUA500PDR-S

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	325 W
Rated Power In Va	500 VA
Output Connector Type	Hard Wire 3-wire (H N + E) 1
Battery Type	Lead-Acid battery
Provided Equipment	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable

Batteries & Runtime

Run Time	View Runtime Graph
Extendable Run Time	0
Included Battery Modules	1
Battery Slots Empty	1
Typical Recharge Time	2 h
Rbc Quantity	1
Battery Life	3...5 year(s)
Replacement Battery	APCRBC135
Battery Charge Power (Watts)	60 W rated

General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

Physical

Height	5.83 in (14.8 cm)
Width	14.25 in (36.2 cm)

Depth	6.73 in (17.1 cm)
Net Weight	28.35 lb(US) (12.86 kg)
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Efficiency At Full Load	75...154 V adjustable 82...144 V
Number Of Input Connectors	1 Hard Wire 3-wire (1PH+N+G)
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic Distortion	Less than 5%
Maximum Configurable Power In Va	500 VA
Max Configurable Power (Watts)	325 W
Topology	Line Interactive
Wave Type	Sine wave
Efficiency At Full Load	94 % full load)
Output Frequency (Sync To Mains)	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

Conformance

Product Certifications	UL Recognized
------------------------	---------------

Environmental

Acoustic Level	55 dBA
Heat Dissipation	90 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Ip Degree Of Protection	IP20
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control Panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Emergency Power Off (Epo)	Yes
Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Category	09305-INDUSTRIAL UPS
Discount Schedule	IUPS
Gtin	731304733010
Returnability	No
Country Of Origin	PH

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.69 in (29.7 cm)
Package 1 Width	18.94 in (48.1 cm)
Package 1 Length	11.69 in (29.7 cm)
Package 1 Weight	29.37 lb(US) (13.32 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov