

58160D

Outdoor Wireless Contact/Transmitter

The 5816OD is a robust, weatherproof, water-resistant outdoor wireless transmitter that provides excellent detection and performance in extreme temperatures. The 5816OD also contains two unique zones. The first loop is a normally closed circuit contact that can have external devices wired directly to the terminal block. The second loop is a built-in magnetic reed switch that can be used to protect gates, sheds, detached garages or any other outdoor area with an exit/entry point. This product provides an ideal way to protect outdoor equipment when using outdoor rated magnetic pull apart contacts. With its dark gray housing, the 5816OD blends well with most outdoor surroundings and can be custom-painted* to match its mounting surface.



58160D

Features & Benefits

- Weather-proof and water-resistant housing makes it ideal for harsh outdoor climates
- Wide magnet gap to facilitate easier installation
- Easily replaceable batteries to minimize truck rolls
- · Built-in reed switch contact loop

- Built-in wired closed contact loop (for use with external devices)
- Tamper protection-removal of front cover and transmitter from mounting plate
- · Screw mountable
- Stainless steel or nylon cable tie mountable (ties not included)

- Magnet, magnet spacer and batteries included
- Paintable* plastic housing to match any surface
- Approved for UL Commercial Burglary listed control panels and receivers

Technical Specifications

Tamper: Cover and rear (wall)

Operating Environment: -40 °F to 150 °F (-40 °C to +66 °C) at RH of 100%

Moisture Resistance: NEMA 4X rated

Maximum Magnet Gap: 1.75 in gap on wood, vinyl, and plastic (1.25 in on steel)

Power: Two (2) 1.5 VDC Energizer® Ultimate LITHIUM AA batteries

Dimensions: (H x W x D)

Sensor: 43% in x 21/16 in x 19/16 in (111 mm x 52 mm x 40 mm)

Magnet (w/ spacer): $4^{1/16}$ in x $1^{5/16}$ in x $1^{7/32}$ in (103 mm x 24 mm x 40 mm)

Operating Wireless Frequency: 345 MHz

Agency Listings: UL 634, UL 1023

ORDERING

58160D	Outdoor Wireless Contact/Transmitter
58160D-MAG	Spare Magnet with Spacer for 58160D
462	1.5 V AA Non-Rechargeable Lithium Battery

