

## Keystone Faceplates Adapters & Mounting Hardware

Signamax Connectivity Systems offers one of the broadest selections of field configurable, flush mount faceplates and multimedia surface mount boxes. From single gang faceplates to multimedia surface mount multi-port boxes; Signamax has the solutions to fit your needs.


### 106 Type Faceplates and Keystone Adapters

PART NUMBER	DESCRIPTION
SKF-106	Single Gang 106 Type Faceplate
106A-2	2-Port 106 Type Keystone Adapter
106A-4	4-Port 106 Type Keystone Adapter

Standard color: IV

For other colors add the following to P/N: WH

The 106 Type Faceplates with 2- and 4-Port Adapters are compatible with all Signamax keystone jacks and multimedia modules. The 106 type plates and adapters are ideal to coordinate electrical wiring devices with structured wiring outlets.




### Decora Style Faceplates and Keystone Adapters

PART NUMBER	DESCRIPTION
SKFD-1	Single Gang Decora Style Faceplate
DKFD-2	Double Gang Decora Style Faceplate
DA-2	2-Port Decora Style Keystone Adapter
DA-3	3-Port Decora Style Keystone Adapter
DA-4	4-Port Decora Style Keystone Adapter

Standard color: IV

For other colors add the following to P/N: WH

Decora Style Faceplates and Adapters are compatible with all Signamax keystone jacks and multimedia modules, Faceplates are available in single and double gang versions. Adapters are available in a 2-, 3- or 4-ports and are ideal for combining data, voice, audio and video in one outlet location.



### Surface Mount Faceplate Boxes

PART NUMBER	DESCRIPTION
SMB1-SG	Single Gang Surface Mount Faceplate Box
SMB1-DG	Double Gang Surface Mount Faceplate Box

Standard color: IV

For other colors add the following to P/N: WH

Surface mount faceplate boxes are available to accommodate both single gang and double gang faceplates. Boxes provide knock outs on all sides for easy cable entry and are supplied with mounting hardware.



## SPECIFICATIONS

### CONSTRUCTION

Fire retardant thermoplastic, steel

### MOUNTING DIMENSIONS

Mounting screw holes distance – 3.28"

### KEYSTONE MODULE MOUNTING DIMENSIONS

Standard keystone footprint

### OVERALL DIMENSIONS

Single gang: 2.75" W x 4.50" H  
Double gang: 4.60" W x 4.50" H

### OPERATING TEMPERATURE

-14°F – 140°F (-10°C – +60°C)