



 DATASHEET

# P-touch EDGE Industrial Handheld Label Printers

The Right Tool  
for the Job

## Product SKUs

PT-E310BTVP

PT-E510VP

PTE560BTVP

 P-TOUCH EDGE INDUSTRIAL  
HANDHELD LABEL PRINTERS

## The Right Tool for the Job

Get the job right the first time with the fully loaded and powerfully intuitive P-touch EDGE. Leverage databases<sup>1</sup> and apply them to industrial label applications, then opt to print strips of easy-to-apply labels with half-cuts. With durable, laminated labels and a comfortable strap to help prevent drops, P-touch EDGE is built to tackle your tough labeling jobs.



	Max Media Width	USB-C	Bluetooth	Cutter	Database	Barcodes	Battery Charge Time	Drop Protection
<b>PT-E310BTVP</b>	18mm	✓	✓	Manual Cut / Pause	✓	QR & 1D	3 hours <sup>4</sup>	Wrist strap
<b>PT-E510VP</b>	24mm	✓		Automatic Dual Cutter	✓	QR & 1D	3 hours <sup>4</sup>	Hand strap
<b>PT-E560BTVP</b>	24mm	✓	✓	Automatic Dual Cutter	✓	QR & 1D	3 hours <sup>4</sup>	Hand strap

## Key features



**Reduce errors:** Store databases<sup>1</sup> and templates in the printer to quickly and accurately create labels from existing work.



**Label it once:** Tackle industrial jobs with durable laminated labels & heat shrink tubes designed to stay in place and options to print from 6mm to 24mm wide.



**Work your way:** Choose to design and print from your phone, computer or directly on the printer.



**Boost drop-protection:** Secure the printer with the ambidextrous hand strap with utility ring or wrist strap to help prevent accidental drops.



**Save time & money:** Get the job done fast with the dual auto-cutter with half-cut that makes peel-and-apply easy in select models.

Learn more about the  
P-touch EDGE Handheld  
Industrial Printer Series



## Industry applications

Fully loaded and powerfully intuitive, P-touch EDGE industrial label printers produce durable identification labels and more.



### Low Voltage

- Cable wraps & flag labels
- Patch panel labeling
- Fiber cable labels
- Equipment, cabinet & rack labels
- Heat shrink tube
- Sequentially numbered connections

### Electrical

- Wire wraps & flags
- Electrical panel labels
- Faceplates
- Heat shrink tube
- Terminal blocks & strips
- Sequentially numbered connections
- Grounding & bonding
- Outlet covers
- Ports
- Conduit & pipe marking

### MRO

- Asset management labels
- Part number labels
- Tools/parts identification
- Component labels
- Calibration labels
- Wire marking



### Laminated tapes

Print durable labels laminated during the printing process with options up to 24mm (0.94in) TZE standard, extra strength and Flex ID tapes and contractor pack HGe tapes.



### Heat shrink tubes

With a 3:1 shrink ratio, HSe tubing can shrink to a third of its size when heat is applied, to pass over connectors and still shrink down to fit snug on the cable.



### And more...

From SLe self-laminating tapes to Ste stencil tapes, and even tamper-evident tapes, Brother offers a wide variety of specialty tapes for your application.



Find the right  
tape for your job

## Get in contact

800-543-6144  
MobileSales@Brother.com  
BrotherMobileSolutions.com

## Brother Label Design Software and Apps<sup>2</sup>



P-touch Editor



Pro Label Tool



Mobile Transfer Express

	PT-E310BTVP	PT-E510VP	PTE560BTVP
<b>Type of Printer</b>	Industrial Wireless Handheld Label Printer	Industrial Handheld Label Printer	Industrial Wireless Handheld Label Printer
<b>Print Width</b>	0.62in (15.8mm)	0.71in (18mm)	
<b>Lines per Label</b>	Up to 5 Lines	Up to 7 Lines	
<b>Media</b>	HGe & TZe Tapes, HSe Heat Shrink Tube, STe Stencil	HGe & TZe Tapes, HSe Heat Shrink Tube, STe Stencil, SLe Self-Laminating	
<b>Media Sizes (width)</b>	3.5mm, 6mm, 9mm, 12mm, 18mm	3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm	
<b>Included Computer Software<sup>2</sup></b>	Windows® Printer Driver, P-touch Editor v6.x for Windows®, P-touch Editor v5.x for Windows® (with Cable Labeling Wizard), Transfer Manager v2.x for Windows®, Printer Setting Tool for Windows®, Transfer Express for Windows®, Update Software for Windows®, Driver Deployment Wizard for Windows®, Firmware Update Tool for Windows® & Mac®		
<b>Memory</b>	Download: Up to 99 Templates, Databases & Images (6MB) Standalone: Up to 99 Files (1,800 Characters / File)		
<b>Operating Systems</b>	Computer: Windows® 11/10 (32/64 bit) Mac® macOS 12.x or Later Mobile: Android™ 10 or Later, iOS® 16 or Later	Computer: Windows® 11/10 (32/64 bit) Mac® macOS 12.x or Later	Computer: Windows® 11/10 (32/64 bit) Mac® macOS 12.x or Later Mobile: Android™ 10 or Later, iOS® 16 or Later
<b>Maximum Print Resolution</b>	180x180 dpi (Standalone & Computer)	180x180 dpi (Standalone), 180x360dpi (Computer)	
<b>Mobile Apps<sup>2</sup></b>	Pro Label Tool for Android™ & iOS® iLink&Label for Android™ & iOS® Mobile Transfer Express for Android™ & iOS® Print SDK Demo for Android™	None	Pro Label Tool for Android™ & iOS® iLink&Label for Android™ & iOS® Mobile Transfer Express for Android™ & iOS® Print SDK Demo for Android™
<b>SDK Support</b>	Windows®, Android™, iOS®	Windows®	Windows®, Android™, iOS®
<b>Interfaces (Profile)</b>	USB Type-C®, Bluetooth® Ver. 5.0 (SPP) / MFi (iAP)	USB Type-C®	USB Type-C®, Bluetooth® Ver. 5.0 (SPP) / MFi (iAP)
<b>Display</b>	128 x 56 Back-Lit Graphic LCD (15 Characters x 2 Lines)	240 x 120 Back-Lit Graphic LCD (17 Characters x 2 Lines) with Real Print Preview Feature	
<b>Keyboard</b>	QWERTY Layout with Rubber Keys		
<b>Cutter</b>	Manual Lever Cutter with Cut / Pause Feature	Automatic with Multi-Label Strip Half-Cutter	
<b>Print Speed<sup>3</sup></b>	Up to 0.8ips (20mm/sec)	Up to 1.2ips (30mm/sec) <sup>4</sup>	
<b>Function Keys</b>	6 keys, 12 functions (General, Faceplate, Cable Wrap / Heat Shrink Tube / Barcode, Cable Flag / Serialize, Patch Panel / Terminal Strip / Advanced Serialization, Punch Block / Database)	10 keys, 13 functions (General, Faceplate, Cable Wrap / Heat Shrink Tube, Cable Flag, Patch Panel / Terminal Strip, Punch Block, Barcode, Serialize, Advanced Serialization, Database, Self-Laminate)	
<b>Copy / Serialization</b>	Up to 99 / 1-2 Fields Individually/Simultaneously (Alpha-Numeric)		
<b>Resident Fonts</b>	7 (Helsinki, Brussels, Los Angeles, Atlanta, Adams, Sofia, Letter Gothic)	14 (Helsinki, Brussels, US, Los Angeles, San Diego, Florida, Calgary, Belgium, Atlanta, Adams, Brunei, Sofia, Germany, Letter Gothic)	
<b>Font Sizes / Styles</b>	8 Sizes / 10 Styles (Standalone)	9 Sizes / 10 Styles (Standalone)	
<b>Rotated Characters</b>	Up to 16 Alpha-Numeric Characters (on 18mm Tape)	Up to 25 Alpha-Numeric Characters (on 24mm Tape)	
<b>Invert, Mirror &amp; Vertical Printing</b>	Yes		

	PT-E310BTVP	PT-E510VP	PTE560BTVP
<b>Resident Barcodes</b>	1D (9): Code39, Code128, I-2/5 (ITF), UPC-A/E, EAN-8/13, GS1-128 (UCC/EAN-128), CODABAR (NW-7) 2D (2): QR Code, Data Matrix		
<b>Symbol Library</b>	477 (59 Voice / Data and Audio Visual, 109 Electrical, 104 Safety, 205 Misc.)		
<b>Drop Prevention</b>	Wrist Strap	Hand Strap (Left / Right)	
<b>Product Dimensions / Weight</b>	5.31in x 9.27in x 2.76in (135mm x 236mm x 70mm) / 1.73lbs. (0.8kg) without Tape Cassette & Battery	5.19in x 9.61in x 3.15in (132mm x 244mm x 80mm) / 2.31lbs. (1.1kg) without Tape Cassette & Battery	
<b>Energy Efficiency</b>	Energy Star Certified		
<b>Power Supply</b>	BA-E001 Li-ion Battery Pack (Standard), PA-AD-004 USB-C PD AC Adapter (Optional)		
<b>Battery Charge Time</b>	As fast as 3 hours <sup>4</sup>		
<b>Operating Temperature / Humidity</b>	50° F to 95° F (10° C to 35° C) / 20% to 80% Non-Condensing		
<b>Box Contents</b>	Protective Case, Wrist Strap, Li-ion Battery, USB-C Cable, Patch Panel Ruler, TZeFX241 Tape	Protective Case, Hand Strap, Li-ion Battery, USB-C Cable, Patch Panel Ruler, TZeFX251 Tape	
<b>Warranty</b>	2-Year Limited Exchange Warranty		

<sup>1</sup> A CSV database file is required for the database functionality in the printer and for the Pro Label Tool app. P-touch Editor for Windows is compatible with the following database file formats: txt, CSV, xls, xlsx, mdb and accdb.

<sup>2</sup> Additional download and wireless connection may be required. Compatibility may vary by device, operating system and label printer used.

<sup>3</sup> Based on performance tests using Brother certified media, actual results may vary by application.

<sup>4</sup> When using optional wall charger PA-AD-004.  
All specifications subject to change without notice.

All trademarks and registered trademarks referenced herein are the property of their respective companies.