



WattBox IP Power Conditioner 12 Controlled Outlets

Power is at the heart of every install, so choose a conditioner that does it all. This WattBox features 12 IP-enabled, individually controllable outlets which can be rack mounted at virtually any angle for complete customization. Add in robust surge protection and a dealer-centric smart outlet design, and you have a power conditioner built for every job in the queue.

SMART POWER INNOVATION

Take control of your installs with IP Power. WattBox and OvrC work together to help you remotely troubleshoot and solve problems, reduce truck rolls, and limit service calls. Through the easy-to-use OvrC desktop or mobile app, you're able to reboot devices and quickly fix common issues to keep your customer's system running smoothly

SMART OUTLET DESIGN

Bulky wall wart power supplies can get in the way and create install headaches. That's why WattBox outlets are spaced out and turned 180 degrees, so each one can be used. We even include tie-down straps and a locking IEC cord to keep everything in place.

MOUNTING FLEXIBILITY

Stop struggling to reach outlets. Whether you need it up, down, angled, or recessed, the WattBox back-of-rack design provides almost limitless options. Turn the included bracket around to easily mount it in the back of a cabinet or on a wall. Or face the bracket down, apply the included feet, and you can quickly secure it to a shelf or the top of the cabinet. The possibilities are endless!

SURGE PROTECTION

From Noise Filtration to 6,480 joules of surge protection, this professional-grade WattBox is engineered to protect critical equipment on the job. Safe Voltage protects gear by automatically disconnecting it during unsafe voltage conditions, while ceramic-encased MOVs provide critical surge protection.

WattBox IP Power Conditioner 12 Controlled Outlets

WB-700-IPV-12

EMI/RF Filtration	Filter Banks 1: 53 dB, 1kHz to 1mHz
Outlets	Type: NEMA 5-15 Number of Outlets: 12 IP Controlled Outlets: 12
Peak Impulse Current	396,000A
Certifications	UL 60950-1, UL 1449, UL 498, UL 497A/B, UL 1283
Dimensions (W x H x D)	17.02" x 3.47" x 3.47"
Features	Surge Component: Ceramic Encased MOV Protection Modes: L-N, L-G, N-G Disconnect Circuitry: Yes
Inputs	AC Input Connection: IEC C-14
Operating Temperature	14°F to 104°F
Power Cord Length	6 Ft.
Line Voltage	120V, 50/60Hz
Ratings	Circuit Breaker Rating: 15A UL Current Rating: 12A Voltage Protection Rating: 500V Joule Rating: 6480 Joules
Rack Spacing	2U
Fuse Type	Thermal Fuse