

Indoor/Outdoor Cross-Connect Wire

XCW



Product Description

Indoor/Outdoor Cross-Connect Wire is intended for cross-connecting points in building entrance enclosures at subscriber's premises and/or in Outside Plant (OSP) enclosures. Each insulated conductor is identified by a combination of solid insulation color, except as noted.

Specifications	
Conductor	Solid bare copper
Insulation	Semi-rigid PVC
Individual Nominal Diameter in (mm)	0.036 (0.9)
Package	Spool
Standards Compliance	UL 444 Listed as CM RoHS-compliant

Part Numbers and Physical Characteristics						
Part Number	Pair Count	AWG (mm)	Wire Color	Overall Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)
02-111-13	1	22 (0.64)	White/Blue	0.07 (1.8)	4 (9)	1,000 (305)
02-102-13	1	22 (0.64)	Yellow/Blue	0.07 (1.8)	4 (9)	1,000 (305)
02-E02-13	1	22 (0.64)	Yellow/Blue	0.07 (1.8)	4 (9)	3,000 (915)
02-113-13	1	22 (0.64)	White/Red	0.07 (1.8)	4 (9)	1,000 (305)
02-114-13	1	22 (0.64)	White/Black	0.07 (1.8)	4 (9)	1,000 (305)
02-513-13*	1	22 (0.64)	White/Red	0.07 (1.8)	4 (9)	1,000 (305)
02-514-13*	1	22 (0.64)	White/Black	0.07 (1.8)	4 (9)	1,000 (305)
02-120-13	2	22 (0.64)	White/Blue, White/Orange	0.11 (2.8)	9 (20)	1,000 (305)
03-H12-13	1	22 (0.64)	White/Violet	0.07 (1.8)	3 (7)	400 (122)
02-G11-13	1	22 (0.64)	White/Blue	0.07 (1.8)	3 (7)	400 (122)
02-G50-13	1	22 (0.64)	White/Orange	0.07 (1.8)	3 (7)	400 (122)
02-H13-13	1	22 (0.64)	Red/White	0.07 (1.8)	3 (7)	400 (122)
02-G16-13	1	22 (0.64)	Violet/Blue	0.07 (1.8)	3 (7)	400 (122)
02-706-13*	1	24 (0.51)	White/Red	0.07 (1.8)	3 (7)	1,000 (305)
02-001-13	1	24 (0.51)	White/Blue	0.07 (1.8)	3 (7)	1,000 (305)
02-050-13	1	24 (0.51)	White/Orange	0.07 (1.8)	3 (7)	1,000 (305)
02-006-13	1	24 (0.51)	White/Red	0.07 (1.8)	3 (7)	1,000 (305)
02-D06-13	1	24 (0.51)	White/Red	0.07 (1.8)	3 (7)	600 (183)
02-053-13	1	24 (0.51)	Red/Blue	0.07 (1.8)	3 (7)	1,000 (305)
02-004-13	1	24 (0.51)	Red/Green	0.07 (1.8)	3 (7)	1,000 (305)
02-005-13	1	24 (0.51)	Red/Slate	0.07 (1.8)	3 (7)	1,000 (305)
02-054-13	1	24 (0.51)	Red/Black	0.07 (1.8)	3 (7)	1,000 (305)
02-702-13*	1	24 (0.51)	Red/Black	0.07 (1.8)	3 (7)	1,000 (305)
02-002-13	1	24 (0.51)	Yellow/Blue	0.07 (1.8)	3 (7)	1,000 (305)
02-409-13	1	24 (0.51)	Blue/Black	0.07 (1.8)	3 (7)	3,000 (915)
02-401-13	1	24 (0.51)	White/Blue	0.07 (1.8)	3 (7)	3,000 (915)
02-450-13	1	24 (0.51)	White/Orange	0.07 (1.8)	3 (7)	3,000 (915)
02-051-13	1	24 (0.51)	White/Green	0.07 (1.8)	3 (7)	1,000 (305)
02-052-13	1	24 (0.51)	White/Black	0.07 (1.8)	3 (7)	1,000 (305)
02-006-13	1	24 (0.51)	White/Red	0.07 (1.8)	3 (7)	1,000 (305)
02-D02-13	1	24 (0.51)	Yellow/Blue	0.07 (1.8)	3 (7)	600 (183)
11-001-02	1	24 (0.51)	White/Blue	0.07 (1.8)	3 (7)	1,000 (305)
11-001-03	1	24 (0.51)	White/Green	0.07 (1.8)	3 (7)	2,000 (610)
02-222-13	2	24 (0.51)	White/Blue, White/Orange	0.10 (2.5)	6 (13)	1,000 (305)
02-221-13	2	24 (0.51)	Red/Blue, Red/Orange	0.10 (2.5)	6 (13)	1,000 (305)
02-224-13	2	24 (0.51)	Yellow/Blue, Yellow/Orange	0.10 (2.5)	6 (13)	1,000 (305)
02-223-13	2	24 (0.51)	White/Orange, White/Green	0.10 (2.5)	6 (13)	1,000 (305)
02-032-13	3	24 (0.51)	White/Blue, White/Orange, White/Green	0.12 (3.0)	9 (20)	1,000 (305)
02-D30-13	3	24 (0.51)	White/Blue, White/Orange, White/Green	0.12 (3.0)	9 (20)	600 (183)
02-041-13	4	24 (0.51)	White/Blue, White/Orange, White/Green, White/Brown	0.15 (3.8)	13 (29)	1,000 (305)

*Solid color (not band marked)