

CEILING LOUDSPEAKER

Quam C5/B70/W

C5/B70/W consists of an 8" O.D., dual cone loudspeaker with a 5 oz. magnet, a 4W, 70V transformer, and a round, screw-mount, steel baffle with a white, powder coat finish. It is designed for paging/intercom applications that require a high efficiency speaker and clear, accurate sound.



| | | |
|------------------------------------|--|---|
| APPLICATION | Intended Use: Program Material: | Indoor environment Signal tones, voice and music |
| AUDIO PERFORMANCE | Average Sensitivity: Loudspeaker Power Rating: Maximum Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection: | 92 dB SPL, 1W/1M 12W RMS, EIA 426A Standard 15W @ 8 Ohms 98dB SPL, 4W/1M BeFe Ceramic, 5 oz. Nominal 65Hz - 17 kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads |
| COMPONENT | Dimensions: Combined Weight: Loudspeaker Model: Loudspeaker Specs: Transformer: Baffle: Finish: | 12 7/8" (Diameter) x 2 1/2" (H) 3.5 lbs. 8C5PAX 8" O.D. loudspeaker, 5 oz. magnet TBL70: 4W, 70V, with 5 taps (0.25W, 0.50W, 1.0W, 2.0W, 4.0W) BR8W: round, steel, screw-mount White powder coat finish |
| RECOMMENDED QUAM COMPONENTS | Enclosures: Mounting Supports: | ERD-8, ERD8U SSB-2, SSB-3, SSB-7 |

