



# 4K H.265 Wall Mount NVR with Facial Recognition and Smart Analytics

## N8WNRE

8 Channel Facial Recognition Wall Mount NVR with 8 Built-in PoE Ports

## N16WNRE

16 Channel Facial Recognition Wall Mount NVR with 16 Built-in PoE Ports

## N8WNREM

8 Channel Facial Recognition Wall Mount NVR with 8 Built-in PoE Ports and Monitor

## N16WNREM

16 Channel Facial Recognition Wall Mount NVR with 16 Built-in PoE Ports and Monitor



N8WNRE



N16WNRE



Compatible Apps



I-VIEW NOW **immix**

### Key Features

- EZ Wizards:** For ease of use and setup
- Camera:** Quickly discover and install all Speco Blue IP cameras
- Setup:** Quick setup of general settings
- Network:** Setup and port forwarding
- Record:** Setup recording resolutions and recording type
- EZ Search 2.0:** Quickly find an event using time-sliced thumbnail images of your recordings with quick preview
- Copy:** Quickly copy what you are playing onto a USB flash drive
- EZ Mobile:** Easy mobile setup for viewing on desktop or mobile apps
- Real time recording up to 8MP resolution (4K) at 30fps
- H.265 compression - Store up to 2x more than H.264!
- 4K HDMI out and one VGA monitor output,
- N8WNRE: 1 SATA port for up to 16TB of storage max
- N16WNRE: 2 SATA ports for up to 32TB of storage max
- Facial Recognition and Comparison\*\*
- Human and vehicle detection\*
- Object and line crossing detection and alerts\*
- Smart Search - Specify a region on the camera view and search on changes in that area\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, Apple TV, Amazon Fire TV, or your mobile device
- Easy video exporting via USB
- Remote control included
- 5 year limited warranty
- \*with Speco Blue Smart Analytic Cameras
- \*\*with Speco Facial Recognition Cameras

### Storage: 2TB - 16TB

N8WNRE2TB	N8WNRE12TB	N16WNRE6TB	N16WNRE12TB
N8WNRE4TB	N8WNRE12TB	N16WNRE8TB	N16WNRE16TB
N8WNRE6TB	N16WNRE2TB	N16WNRE24TB	
N8WNRE8TB	N16WNRE4TB	N16WNRE32TB	
N8WNREM2TB	N8WNREM12TB	N16WNREM6TB	N16WNREM12TB
N8WNREM4TB	N8WNREM12TB	N16WNREM8TB	N16WNREM16TB
N8WNREM6TB	N16WNREM2TB	N16WNREM24TB	
N8WNREM8TB	N16WNREM4TB	N16WNREM32TB	

### Additional Features

- Find and install IP cameras on the local network without needing to locate the cameras manually
- Supports different recording types: Continuous, Motion, Analytics, and Sensor
- Create bookmark pins on playback for easy reference
- Instant playback for individual channels directly from the live view screen
- Customizable channel view placement
- Remote monitoring, recording, playback, configuration, upgrades, and PTZ control via the internet
- Simultaneous HDMI & VGA video output (N8WNRE & N16WNRE)
- Supports 2-way audio communication (speaker required)

### Optional Accessories





# Technical Specifications: 4K H.265 NVR Wall Mount Smart NVR with PoE

Model		NRE		
Video	Input	Max. IP Channels	8	16
		IP Camera	H.264/H.265 Auto Detection (Max. 8MP)	
	Output	Main Monitor	HDMI (Max. 4K) and VGA (Max. Full HD)	
Sub Monitor		n/a		
Audio	Network Input		8 Ch. IPC audio input	16 Ch. audio input
	2-way Audio		RCAx1	
	Local Output		RCAx1	
	Encoding Resolutions		8MP/5MP/4MP/3MP/1080P/720P	
Recording	Codec		H.264/H.265 (Auto Detection)	
	Max Frame Rate per Channel		Any Resolution @30fps	
	Recording Mode		Analytics/Continuous/Motion/Sensor/Schedule/Manual	
	Pre-Recording		Max. 5 seconds	
	Post Recording		Max. 10 minutes	
Search & Playback	Search		EZ Search, Motion, Specific Date/Time, Event, Museum, Bookmarks, Snapshots, Log	
	Simultaneous Playback		Max. 8 Ch.	
	Smart Search		Highlighted color to display camera records in a certain period of time, different colors refer to different record events	
	Playback Resolutions		8MP/5MP/4MP/3MP/1080P/720P	
	Playback Functions		Play, pause, FF, FB, digital zoom, etc.	
Backup	Media		USB drive, USB Portable HDD, Network	
	Format		JPG, AVI, ZIP (Player+Proprietary Data)	
Storage	HDD	Max Capacity of each HDD	16TB	
		Internal SATA ports	1	2
	USB	Front	1 USB 2.0	
		Rear	1 USB 3.0	
Alarm	Mode		Manual, sensor, motion, exception, intelligence	
	Input/Output		Input: 8 Ch. local / Output: 4 Ch. local	
	Linkage		Record/Snapshot/Preset/Email/Pop-up Window	
User I/F	Input Method		IR Remote, Mouse	
Network	Network Bandwidth		80Mbps	160Mbps
	P2P/Dynamic DNS		Free US-Based Speco P2P and DDNS Service	
	Network Protocols		TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP	
Network Access	Mobile		iOS/Android via Speco Blue App	
	Other Viewing Platforms		Apple TV and Amazon Fire TV	
	Web Viewer		Windows IE	
	VMS		SecureGuard®	
	Max. User Access		Max 10 users online (web client)	
Features	Digital Zoom		Live and Playback, Free Size	
	Smart Analysis		* **Facial Recognition, Crowd Density, People Counting, Object Detection, Tampering, Tripwire, Intrusion	
	S.M.A.R.T		Temperature, Power On Time, Bad Sectors and Health	
Power	Power Consumption		≤ 15W (without HDD)	
	PoE Ports		8	16
	Power Per PoE Ports		15W	15W
	Total PoE Power Budget		96W	150W
Environment	Operating Temperature		14°F to 122°F (-10°C to 50°C )	
	Operating Humidity		10% ~ 90% humidity	
Dimensions	Unit	387mm x 298mm x 89mm (15.25" x 11.75" x 3.5")	489mm x 413mm x 89mm (19.25" x 16.25" x 3.5")	