


960H Color or Standard BW Angle Mount Camera

CVC695AM 3.6mm wide angle lens, horizontal 72° / vertical 53°, color


CVC95AM 3.6mm wide angle lens, horizontal 72° / vertical 53°, BW

Features

- Weather/tamper resistant cover
- Features a 3.6mm wide angle lens that views at a downward angle of 38°
- Includes tamper resistant screw for vandal resistant mounting
- 700 TV lines of resolution
- 5 year warranty



2.5" (L)



2.75" (H)

2.25" (W)

Specifications

CVC695AM

Image Sensor 1/3" Sony Super HAD II™ color CCD
 Resolution..... 700 TV lines
 Minimum Illumination..... 0.001 lux (sense-up)
 Effective Pixels 976 (H) x 494 (V)
 Electronic Shutter Speed..... Auto: 1/60 sec. – 1/100,000 sec.
 Video Output..... 1.0Vp-p / 75 ohms
 S/N Ratio More than 52dB
 Scanning Frequency..... 15.75kHz (H) / 60Hz (V)
 Output..... Video - BNC, Power - DC jack
 Operating Temperature/
 Humidity..... 14° F – 122° F / within 95% RH
 Power Consumption 210mA
 Power Supply 12VDC (UL and CSA listed
 power supply included)
 Housing 18 gauge stainless steel
 Dimensions..... 2.25" (W) x 2.75" (H) x 2.5" (L)
 Weight 6.8 oz.

CVC95AM

Image Sensor 1/3" BW CCD
 Resolution..... 420 TV lines
 Minimum Illumination..... 0.02 lux
 Effective Pixels 512 (H) x 492 (V)
 Electronic Shutter Speed..... Auto: 1/60 sec. – 1/100,000 sec.
 Video Output..... 1.0Vp-p / 75 ohms
 S/N Ratio More than 50dB
 Scanning Frequency..... 15.75kHz (H) / 60Hz (V)
 Output..... Video - BNC, Power - DC jack
 Operating Temperature/
 Humidity..... 14° F – 122° F / within 95% RH
 Power Consumption 150mA
 Power Supply 12VDC (UL and CSA listed
 power supply included)
 Housing 18 gauge stainless steel
 Dimensions..... 2.25" (W) x 2.75" (H) x 2.5" (L)
 Weight 6.8 oz.

Optional Lenses

CVC95AM2.5.....2.5mm lens
 CVC95AM6.....6mm lens
 CVC95AM8.....8mm lens
 CVC95AM12..... 12mm lens

CVC695AM2.5...2.5mm lens
 CVC695AM2.9...2.9mm lens
 CVC695AM6.....6mm lens
 CVC695AM8.....8mm lens
 CVC695AM12.... 12mm lens