

# **HD-TVI 2MP Intensifier® Bullet Cameras** with Junction Box

## HTi70TM

2.8-12mm motorized lens, dark gray housing

### HTi702TM

5-50mm motorized lens, dark gray housing

#### **Features**

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets: Outdoor, Low Light, Hallway, Lobby, Elevator, Indoor Built-in heater and anti-fog glass reduces condensation

- 3-axis for wall and ceiling mounting
- Full OSD operation through on-board control and UTC (up the coax)
- Additional 960H analog
- Signal distance up to 1600
- IP67 compliant, weather
- 12VDC & 24VAC dual voltage operation
- 5 year warranty



Included Junction Box















#### **Camera Specifications**

Image Sensor	1/3" Progressive Scan CMOS, 2MP
Minimum Illumination	0.001 lux (Sens-up X32)
Effective Pixels	1984 (H) x 1105 (V)
Total Pixels	2000 (H) x 1121 (V)
Scanning System	Progressive
S/N Ratio	More than 50dB
Output Resolution	1920x1080 @ 30fps
Video Output	1.0Vp-p / 75 Ohms
Electronic Shutter	Auto / Manual (1/30 - 1/30,000 sec.)
Day / Night	Color (default) / BW / External / Auto
Test Monitor Output	CVBS (BNC out in Yellow)
Communication	UTC (up the coax)
Power	12VDC / 24VAC
Power Consumption	600mA max. (DC), 450mA max. (AC)
Operating Temperature	-40° F - 140° F
Unit Dimensions	9.64" (L) x 3.72" (Dia.)
Unit Weight	2 lbs (camera), 0.9lbs (junction box)
Certifications	FCC, RoHS
Signal Distance	Up to 1600 feet (depending on coax quality)*

<sup>\*</sup>Products are in compliance with NDAA Section 889 Part B Guidelines

#### Optional Accessories







Power Supply



12VDC Power Supply



TVIUTPPT ID Video Transceive with Pigtail (Balun)





