

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

---

<b>Division 28</b>	Electronic Safety and Security
<b>Section 28 00 00</b>	Electronic Safety and Security
<b>Section 28 20 00</b>	Electronic Surveillance
<b>Section 28 23 00</b>	Video Surveillance

**Notes to Security System Specifiers** - This A&E specification is written according to Construction Specifications Institute (CSI) 3-Part Format, based on MasterFormat™ (2016 Edition) and The Project Resource Manual – CSI Manual of Practice. CSI MasterFormat 2016 incorporates numerous significant changes affecting electronic safety and security. This document is written to provide flexibility in using either format, although adoption of MasterFormat 2016 is encouraged. All trademarks are properties of their respective owners.

---

## Part 1 General

### 1.1. Summary of Requirements

#### A. N8NRT Smart Management Terminal For O2TML

1. The NVR shall collect network IP video and audio from 8 x O2TML Temperature Reading Panel Kiosk with Face and Mask Detection and digitize them for the purpose of display, archive and requested distribution across the Ethernet network.

#### B. Related Requirements

1. Section 28 05 00 Common Work Results for Electronic Safety and Security
2. Section 28 05 19.11 Digital Video Recorders
3. Section 28 05 19.13 Hybrid Digital Video Recorders
4. Section 28 05 19.15 Network Video Recorders
5. Section 28 21 00 Surveillance Cameras
6. Section 28 21 13 IP Cameras
7. Section 28 23 13 Digital Video Recorders and Analog Recording Devices

### 1.2. References

#### A. Abbreviations

1. DDNS Dynamic Domain Name Server
2. DHCP Dynamic Host Configuration Protocol
3. DNS Domain Name Server
4. FTP File Transfer Protocol
5. GUI Graphical User Interface
6. HTTP Hypertext Transfer Protocol
7. HTTPS Secure HTTP
8. ICMP Internet Control Message Protocol
9. IGMP Internet Group Management Protocol
10. IP Internet Protocol

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

---

11. JPEG	Joint Photographic Experts Group
12. MPEG	Moving Pictures Experts Group
13. NAS	Network Attached Storage
14. NIC	Network Interface Controller
15. NTP	Network Time Protocol over Ethernet
16. NVR	Network Video Recorder
17. PoE	Power over Ethernet
18. PPPoE	Point-to-Point Protocol over Ethernet
19. P2P	Peer-to-Peer
20. PTZ	Pan Tilt Zoom
21. QoS	Quality of Service
22. RTP	Real-Time Transport Protocol
23. RTSP	Real-Time Streaming Protocol
24. SD Card	Secure Digital Flash Memory Card
25. SMTP	Simple Mail Transfer Protocol
26. TCP	Transmission Control Protocol
27. UDP	User Datagram Protocol
28. UPnP	Universal Plug and Play
29. VMS	Video Management System
30. ESD	Electrostatic discharge
31. MSIE	Microsoft Internet Explorer
32. HDD	Hard Disk Drive
33. EZ	Easy
34. FF	Fast Forward
35. FR	Fast Reverse
36. DAS	Direct Attached Storage
37. LAN	Local Area Network
38. WAN	Wide Area Network

### 1.3. Certifications, Standards and Ratings

#### A. Reference Standards

1. Networking
  - a. IEEE – 802.3 Ethernet Standards
2. Video
  - a. ISO/IEC 14496 Standards for MPEG-4
  - b. ITU-T Recommendation H.264/H.265

### 1.4. Submittals

#### A. Product Data

1. Provide manufacturer's datasheets in printed or electronic form.
2. Provide manufacturer's Installation and operating manuals/guides.
3. Provide manufacturer's warranty statement.

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

---

### 1.5. Qualifications

#### A. Manufacturer

1. Company specializing in manufacturing products at least ten years experience.

#### C. Supplier

1. Authorized distributor of specified manufacturer with at least 5 years.

#### D. Installer

1. Authorized installer of specified manufacturer with a least 5 years experience.

### 1.6. Delivery, Storage and Handling

#### A. Delivery

1. Deliver materials in original, unopened and undamaged packaging in accordance with manufacturer's instructions.

#### E. Storage

1. Store and guard materials from environmental and temperature conditions in accordance with manufacturer's instructions.

#### F. Handling

1. Handle and operate products and systems in accordance with manufacturer's instructions.

### 1.7. Warranty

#### A. Warranty Period

1. Manufacturer shall warranty NVR (except HDD) for a period of [5] years for the repair or replacement of defective equipment.
2. Manufacturer shall warranty HDD for a period of [3] years.

### 1.8. Certifications

#### B. Certification Types

1. CE (EMC/LVD)
2. FCC, Class A
3. RoHS

### 1.9. Tech Support

#### A. Support

1. Technical support shall be based in North America.
2. Technical support support shall be via email or toll-free phone number.
3. Technical support shall be available weekdays from 6 a.m. to 6 p.m. EST.

## Part 2 Product

### 2.1. Manufacturer

#### A. Manufacturer

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

### Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

---

1. Speco Technologies  
200 New Highway  
Amityville, NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web Site: [www.specotech.com](http://www.specotech.com)

### G. Product

1. NR Series
2. Models:
  - a. N8NRT1TB, N8NRT2TB, N8NRT3TB, N8NRT4TB, N8NRT6TB  
N8NRT8TB, N8NRT10TB

### H. Product Description

1. Designed specifically for AI application management of Speco O2TML Temperature Reading Panel Kiosk such as body temperature measurement management, time attendance, access control, etc. NVR supports real-time face capture display, temperature display and alarm out, statistics, video preview, search and playback.

## 2.2. Product Description

### A. General

1. All equipment and materials used shall be standard components, regularly manufactured, regularly utilized in the manufacturer's system.
2. All systems and components shall have been thoroughly tested and proven in actual use.
3. All systems and components shall be provided with the availability of a toll free technical support phone number from the manufacturer. The phone number shall allow for immediate technical assistance for either the dealer/installer or the end user at no charge.
4. All systems and components shall be provided with an explicit manufacturer warranty.

### B. Description

1. NVR shall support a maximum of 8 user permission groups including Administrator, Advanced and Ordinary which are the default permission groups of the system.
2. NVR shall support real-time display of all abnormal data, including abnormal temperature, mask off, block list, etc.
3. NVR shall support real-time face capture view, face match view, body temperature view.
4. NVR shall support real-time personal information display, including name, area, temperature, mask on/off, company, etc.
5. NVR shall support auto adjustment of the camera's image display proportion
6. NVR shall support audio monitoring of the temperature panel.
7. NVR shall support precise face recognition with masks.

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

8. NVR shall support statistics of abnormal temperature and non-mask detection in recent 24 hours or 7 days.
9. NVR shall support statistics of the people information, including staff, allow list, block list, VIP, stranger and staff counts.
10. NVR shall support adding 20,000 face pictures.
11. NVR shall support face attendance.
12. NVR shall support face greeting via Web client
13. NVR shall support abnormal temperature alarm.
14. NVR shall support non-mask detection alarm.
15. NVR shall support time scale operation in quick playback and the playback date and time can be set randomly by scrolling the mouse; the time interval of the time scale can be zoomed
16. NVR shall support pass-through records search by mask status, by normal/over temperature or by event (stranger/allow list/ block list/VIP).
17. NVR shall simultaneous HDMI & VGA video output
18. NVR shall meet the requirements of business, government and general security surveillance applications.
19. NVR shall offer remote network connectivity to a properly specified PC computer that allows transmission of video and control data over the Ethernet network.
20. NVR shall offer a GUI incorporating video display areas, toolbars, control palettes and site/device trees.
21. NVR shall employ a high profile H.264/H.265 compression algorithm in the video digitizing scheme. Network IP cameras shall be the primary video input devices.
22. NVR shall offer simultaneously view live or playback while continuing to record and network transfer. The NVR shall provide full digital video and audio surveillance over a standard 100Base-T network.
23. NVR shall offer multiple continuously recorded digital video and audio channels onto a hard drive medium. Each channel of video data shall have the capability of being recorded, displayed, played back, archived and distributed simultaneously across the network.
24. The video shall also be capable of alarm notification based on motion via a built-in utility to configure motion detection of objects in the individual camera scenes. Each camera can be customized for motion area and sensitivity using grid blocks through the camera's setup tool. The motion events shall be transmitted to authorized users via an email notification utility.
25. The video shall also have selectable digital zoom on any camera in live view and playback mode. The video recording capability shall be fully scheduled using the built-in utility.
26. NVR shall also have full LAN, WAN and Internet connection capability. The NVR will require a broadband internet connection of a minimum 256 Mbps using either a static or dynamic type IP address. When using a dynamic IP address, DDNS shall be

## A&E Specification

### N8NRT Smart Management Terminal For O2TML

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

- 
- an available feature to track the IP address via a customized URL. The NVR supports TCP/IP and DHCP protocol.
27. NVR shall record user selectable resolution and frame rate set from within the GUI of the IP cameras.
  28. NVR shall utilize a Digital Signature video authentication algorithm. It is a standard authentication that is based on a 128-bit message used to verify data integrity
  29. NVR shall incorporate a series of EZ (easy) features used to simplify installation and configuration of the unit. These features shall include EZ-Setup, EZ-Network, EZ-Camera, EZ-Record, EZ-Copy and EZ-Search.
  30. NVR shall support searching of recorded video from EZ Search, motion events, analytic events, date/time, museum, bookmarks, snapshots and logs.
  31. NVR shall support the following playback functions: play, pause, FF, FR, and Digital Zoom.
  32. On event, NVR shall trigger recording, control PTZ, Alarm Out, Pop-up alarm preview, send email, FTP, record snapshot, and activate buzzer and screen tips.
  33. NVR shall offer a full multi-user authorization logon function. This function shall offer five levels of authorization based on Main Menu functions. There shall be an Administrator and User level offered. Anyone with a correct password shall log into the NVR.
  34. NVR shall offer a GUI capable of complete recorder configuration and operation. Sub-features such as defined video display and control, component setup, recording setup, network setup and the use of dialog messages shall be provided in a comprehensive menu structure.
  35. Operation of the system shall be facilitated by the use of a monitoring screen whereby a security operator can perform a full scope of surveillance duties using the front panel controls and indicators, the remote application software, the CMS software or a mouse.
  36. NVR shall use a HDMI / VGA Main Monitor output for video display sequencing
  37. NVR shall be configurable for several foreign languages, other than English.
  38. NVR shall support the use of PTZ type cameras either on an RS-485 bus using built-in protocols from several manufacturers or through the network of the PTZ IP camera.
  39. NVR shall support alarm in and relay out functions. The alarm events shall be transmitted to users via a built-in email utility.
  40. NVR shall support a variety of different capacity hard drives for a total capacity of 28TB.
  41. The front panel shall contain a lights to indicate status of power on/off, HDD health and network connectivity.
  42. NVR shall contain 2 x USB ports with one available on the front panel and one at the back of the unit.
  43. NVR shall also be equipped for installation in a standard 19 in. (48.2 cm) rack shelf. The rear panel shall contain WAN network port (RJ45) to connect to internet, HDMI

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516 Fax. 1-631-957-3880

Web site: [www.specotech.com](http://www.specotech.com)

---

Main Monitor, VGA Main Monitor Output, Audio In/Out inputs, 2 eSATA, LAN (Network) port, and 2 USB connector.

44. NVR shall support exporting of video in AVI format with a stand-alone player.
45. NVR shall support exporting video to the following media types: DAS and NAS
46. NVR shall support and be equipped with an IR remote control.
47. NVR shall support and include a Multi-Client application for multi-NVR remote access.
48. NVR shall support bi-directional audio.
49. NVR shall meet or exceed the following design and performance specifications
50. NVR shall support multi-time zone and DST.
51. NVR shall support Smart Analytics from Speco Smart Analytic Cameras. Analytics types include Crowd Density, People Counting, Object Detection, Tampering, Tripwire, and Intrusion.
52. NVR shall support S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD).
53. NVR shall support plug-n-play via Speco's free P2P service.
54. NVR shall support DDNS capability via Speco's free DDNS service.
55. NVR shall auto-discover Speco's and other ONVIF Profile S compliant IP cameras on the local network without needing to locate the cameras manually.
56. NVR shall incorporate an embedded Linux® operating system using a proprietary software application for control, management and display.

### C. Electrical Specification

1. Power Input 48VDC
2. Power Supply 48VDC Power Supply
3. Power Consumption ≤ 15W (without HDD)
4. Power Cable USA standard (117 VAC, 3 prongs, 6 ft or 1.8 m)

### D. Environmental Specification

1. Operating Temperatures -10° to 122°F (-23.3° to 50°C)
2. Operating Humidity 10% to 90%, non-condensing

### E. Mechanical Specification

1. System
  - a. Operating System: Embedded Linux
  - b. User Interface: Semi-transparent on-screen graphic overlays
2. Video
  - a. Inputs 8 x O2TML
  - b. Outputs HDMI, VGA
  - c. Encoding H.264, H.265
  - d. Resolutions 8MP/5MP/4MP/3MP/1080P/720P
  - e. Frame Rate 30 fps

# A&E Specification

## N8NRT Smart Management Terminal For O2TML

**Speco Technologies**  
200 New Highway, Amityville NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web site: [www.specotech.com](http://www.specotech.com)

---

f.	Pre-record	5 seconds
g.	Post-record	10 minutes
h.	Display Modes	1x1, 2x2, 3x3, 4x4, Custom
i.	Outputs	1 x HDMI (4K), 1 x VGA
3.	Audio	
a.	Network Inputs	8 audio
b.	MIC Inputs	1 x RCA
c.	Speakers Outputs	1 x RCA
d.	Codec	G.711A/G.711U
4.	Network	
a.	WAN	1 x 1Gbps (RJ45)
b.	LAN	8 x 10/100Mbps (RJ45)
c.	Protocol	TCP/IP, DHCP, DNS, DDNS, UPnP, NTP, SMTP, ONVIF Profile S
5.	PTZ	N/A
6.	Alarms	
a.	Inputs	8
b.	Outputs	4
7.	Auxiliary	
a.	USB	1 x USB 2.0 Port (Front) 1 x USB 2.0 Port (Rear)
8.	Front Panel	
a.	Power Indicator	Power On, Blue
b.	Recording Status	Recording, Blue
c.	Network Indicator	Network access, Blue
9.	User Interface	IR Remote, Mouse
10.	Remote Surveillance	
a.	Web Viewer	MSIE
b.	Control System	Speco Technologies SecureGuard
c.	Mobile Devices	iOS, Android
11.	External Storage	1 x SATA (10TB max each HDD)

## Part 3 Execution

### 3.1 Examination

- A. Device shall be inspected for physical and cosmetic defects.
- B. Package box shall include device, power supply, mouse, remote control unit, installation and user guides on disk.

### **3.2 Preparation**

- A. ESD-sensitive parts shall be properly protected against static buildup through the use of static shielding material.
- B. Package box shall contain adequate padding to prevent damage to device and parts during shipping.

### **3.3 Installation**

- A. Device shall be installed in accordance with the manufacturers' installation guide provided.
- B. Device shall be installed by qualified service professionals.
- C. Device shall be installed in accordance with the National Electric Code or applicable local codes.
- D. Device shall be installed in locations which adequately supports the device's environmental and electrical requirements.

### **3.4 Field Quality Control**

- A. Test for proper communication between device and supporting devices.
- B. Test for proper operation of device's system software and related software programs.
- C. Determine and report all problems to the manufacturers' customer service representatives.

### **3.5 Adjusting**

- A. Make all necessary adjustments to the device and supporting devices to ensure the proper operation of the device.
- B. Make all necessary adjustments to the devices to satisfy end-user requirements.

### **3.6 Demonstration and Training**

- A. Perform final inspection to validate and ensure proper functioning of device.