

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

Division 28	Electronic Safety and Security
Section 28 00 00	Electronic Safety and Security
Section 28 20 00	Electronic Surveillance
Section 28 23 00	Video Surveillance

Notes to Security System Specifiers - This A&E specification is written according to Construction Specifications Institute (CSI) 3-Part Format, based on MasterFormat™ (2016 Edition) and The Project Resource Manual – CSI Manual of Practice. CSI MasterFormat 2016 incorporates numerous significant changes affecting electronic safety and security. This document is written to provide flexibility in using either format, although adoption of MasterFormat 2016 is encouraged. All trademarks are properties of their respective owners.

Part 1 General

1.1. Summary of Requirements

A. N8NRE/N16NRE/N32NRE Network Video Recorder (NVR) with Face Recognition and Smart Analytics

1. The NVR shall collect multiple channels (8, 16, 32) of network IP video, multiple channels of audio and digitize them for the purpose of display, archive and requested distribution across the Ethernet network. The NVR shall also support Facial Recognition and advanced Smart Analytics.
2. The N8NRE and N16NRE shall have 4 and 8 built-in PoE ports respectively.

B. Related Requirements

1. Section 28 05 00 Common Work Results for Electronic Safety and Security
2. Section 28 05 19.11 Digital Video Recorders
3. Section 28 05 19.13 Hybrid Digital Video Recorders
4. Section 28 05 19.15 Network Video Recorders
5. Section 28 21 00 Surveillance Cameras
6. Section 28 21 13 IP Cameras
7. Section 28 23 13 Digital Video Recorders and Analog Recording Devices

1.2. References

A. Abbreviations

1. DDNS Dynamic Domain Name Server
2. DHCP Dynamic Host Configuration Protocol
3. DNS Domain Name Server
4. FTP File Transfer Protocol
5. GUI Graphical User Interface

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

6. HTTP	Hypertext Transfer Protocol
7. HTTPS	Secure HTTP
8. ICMP	Internet Control Message Protocol
9. IGMP	Internet Group Management Protocol
10. IP	Internet Protocol
11. JPEG	Joint Photographic Experts Group
12. MPEG	Moving Pictures Experts Group
13. NAS	Network Attached Storage
14. NIC	Network Interface Controller
15. NTP	Network Time Protocol over Ethernet
16. NVR	Network Video Recorder
17. PoE	Power over Ethernet
18. PPPoE	Point-to-Point Protocol over Ethernet
19. P2P	Peer-to-Peer
20. PTZ	Pan Tilt Zoom
21. QoS	Quality of Service
22. RTP	Real-Time Transport Protocol
23. RTSP	Real-Time Streaming Protocol
24. SD Card	Secure Digital Flash Memory Card
25. SMTP	Simple Mail Transfer Protocol
26. TCP	Transmission Control Protocol
27. UDP	User Datagram Protocol
28. UPnP	Universal Plug and Play
29. VMS	Video Management System
30. ESD	Electrostatic discharge
31. MSIE	Microsoft Internet Explorer
32. HDD	Hard Disk Drive
33. EZ	Easy
34. FF	Fast Forward
35. FR	Fast Reverse
36. DAS	Direct Attached Storage
37. LAN	Local Area Network
38. WAN	Wide Area Network

1.3. Certifications, Standards and Ratings

A. Reference Standards

1. Networking
 - a. IEEE – 802.3 Ethernet Standards
2. Video
 - a. ISO/IEC 14496 Standards for MPEG-4
 - b. ITU-T Recommendation H.264/H.265

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

3. Speco 2.0

1.4. Submittals

A. Product Data

1. Provide manufacturer's datasheets in printed or electronic form.
2. Provide manufacturer's Installation and operating manuals/guides.
3. Provide manufacturer's warranty statement.

1.5. Qualifications

A. Manufacturer

1. Company specializing in manufacturing products at least ten years experience.

C. Supplier

1. Authorized distributor of specified manufacturer with at least 5 years.

D. Installer

1. Authorized installer of specified manufacturer with a least 5 years experience.

1.6. Delivery, Storage and Handling

A. Delivery

1. Deliver materials in original, unopened and undamaged packaging in accordance with manufacturer's instructions.

E. Storage

1. Store and guard materials from environmental and temperature conditions in accordance with manufacturer's instructions.

F. Handling

1. Handle and operate products and systems in accordance with manufacturer's instructions.

1.7. Warranty

A. Warranty Period

1. Manufacturer shall warranty NVR (except HDD) for a period of [5] years for the repair or replacement of defective equipment.
2. Manufacturer shall warranty HDD for a period of [3] years.

1.8. Certifications

B. Certification Types

1. CE (EMC/LVD)
2. FCC, Class A
3. RoHS

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

1.9. Tech Support

A. Support

1. Technical support shall be based in North America.
2. Technical support support shall be via email or toll-free phone number.
3. Technical support shall be available weekdays from 6 a.m. to 6 p.m. EST.

Part 2 Product

2.1. Manufacturer

A. Manufacturer

1. Speco Technologies
200 New Highway
Amityville, NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web Site: www.specotech.com

G. Product

1. NR Series
2. Models:
 - a. N8NRE2TB, N8NRE3TB, N8NRE4TB, N8NRE6TB
N8NRE8TB, N8NRE12TB, N8NRE14TB
 - b. N16NRE2TB, N16NRE3TB, N16NRE4TB, N16NRE6TB
N16NRE8TB, N16NRE12TB, N16NRE16TB, N16NRE24TB
N16NRE28TB
 - c. N32NRE2TB, N32NRE3TB, N32NRE4TB, N32NRE6TB
N32NRE8TB, N32NRE12TB, N32NRE16TB, N32NRE24TB
N32NRE32TB, N32NRE64TB, N32NRE96TB, N32NRE112TB

H. Product Description

1. A 4K H.265 NVR available capable of 8, 16 or 32 channels of video.

2.2. Product Description

A. General

1. All equipment and materials used shall be standard components, regularly manufactured, regularly utilized in the manufacturer's system.
2. All systems and components shall have been thoroughly tested and proven in actual use.
3. All systems and components shall be provided with the availability of a toll free technical support phone number from the manufacturer. The phone number shall

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

allow for immediate technical assistance for either the dealer/installer or the end user at no charge.

4. All systems and components shall be provided with an explicit manufacturer warranty.

B. Description

1. NVR shall meet the requirements of business, government and general security surveillance applications.
2. NVR shall offer remote network connectivity to a properly specified PC computer that allows transmission of video and control data over the Ethernet network.
3. NVR shall offer a GUI incorporating video display areas, toolbars, control palettes and site/device trees.
4. NVR shall employ a high profile H.264/H.265 compression algorithm in the video digitizing scheme. Network IP cameras shall be the primary video input devices.
5. NVR shall offer simultaneously view live or playback while continuing to record and network transfer. The NVR shall provide full digital video and audio surveillance over a standard 100Base-T network.
6. NVR shall offer multiple continuously recorded digital video and audio channels onto a hard drive medium. Each channel of video data shall have the capability of being recorded, displayed, played back, archived and distributed simultaneously across the network.
7. The video shall also be capable of alarm notification based on motion via a built-in utility to configure motion detection of objects in the individual camera scenes. Each camera can be customized for motion area and sensitivity using grid blocks through the camera's setup tool. The motion events shall be transmitted to authorized users via an email notification utility.
8. The video shall also have selectable digital zoom on any camera in live view and playback mode. The video recording capability shall be fully scheduled using the built-in utility.
9. NVR shall also have full LAN, WAN and Internet connection capability. The NVR will require a broadband internet connection of a minimum 256 Mbps using either a static or dynamic type IP address. When using a dynamic IP address, DDNS shall be an available feature to track the IP address via a customized URL. The NVR supports TCP/IP and DHCP protocol.
10. NVR shall record user selectable resolution and frame rate set from within the GUI of the IP cameras.
11. NVR shall utilize a Digital Signature video authentication algorithm. It is a standard authentication that is based on a 128-bit message used to verify data integrity
12. NVR shall incorporate a series of EZ (easy) features used to simplify installation and configuration of the unit. These features shall include EZ-Setup, EZ-Network, EZ-Camera, EZ-Record, EZ-Copy and EZ-Search.

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

13. NVR shall support searching of recorded video from EZ Search, motion events, analytic events, date/time, museum, bookmarks, snapshots and logs.
14. NVR shall support the following playback functions: play, pause, FF, FR, and Digital Zoom.
15. On event, NVR shall trigger recording, control PTZ, Alarm Out, Pop-up alarm preview, send email, FTP, record snapshot, and activate buzzer and screen tips.
16. NVR shall offer a full multi-user authorization logon function. This function shall offer five levels of authorization based on Main Menu functions. There shall be an Administrator and User level offered. Anyone with a correct password shall log into the NVR.
17. NVR shall offer a GUI capable of complete recorder configuration and operation. Sub-features such as defined video display and control, component setup, recording setup, network setup and the use of dialog messages shall be provided in a comprehensive menu structure.
18. Operation of the system shall be facilitated by the use of a monitoring screen whereby a security operator can perform a full scope of surveillance duties using the front panel controls and indicators, the remote application software, the CMS software or a mouse.
19. NVR shall use a HDMI / VGA Main Monitor output for video display sequencing
20. NVR shall be configurable for several foreign languages, other than English.
21. NVR shall support the use of PTZ type cameras either on an RS-485 bus using built-in protocols from several manufacturers or through the network of the PTZ IP camera.
22. NVR shall support alarm in and relay out functions. The alarm events shall be transmitted to users via a built-in email utility.
23. NVR shall support a variety of different capacity hard drives for a total capacity of 28TB.
24. The front panel shall contain a lights to indicate status of power on/off, HDD health and network connectivity.
25. NVR shall contain 2 x USB ports with one available on the front panel and one at the back of the unit.
26. NVR shall also be equipped for installation in a standard 19 in. (48.2 cm) rack shelf. The rear panel shall contain WAN network port (RJ45) to connect to internet, HDMI Main Monitor, VGA Main Monitor Output, Audio In/Out inputs, 2 eSATA, LAN (Network) port, and 2 USB connector.
27. NVR shall support exporting of video in AVI format with a stand-alone player.
28. NVR shall support exporting video to the following media types: DAS and NAS
29. NVR shall support and be equipped with an IR remote control.
30. NVR shall support and include a Multi-Client application for multi-NVR remote access.
31. NVR shall support bi-directional audio.
32. NVR shall meet or exceed the following design and performance specifications

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

33. NVR shall support multi-time zone and DST.
34. NVR shall support Smart Analytics from Speco Smart Analytic Cameras. Analytics types include Human Detection, Vehicle Detection, Facial Recognition, Crowd Density, People Counting, Object Detection, Tampering, Tripwire, and Intrusion.
35. NVR shall support Speco Facial Recognition Cameras.
36. NVR shall support matching of faces detected by facial recognition cameras.
37. NVR shall support identification assignment to faces.
38. NVR shall store faces and shall have the ability to store corresponding information (ie. name, birthday, ID number, phone number).
39. NVR shall support import/export of face database.
40. NVR shall support smart playback of faces.
41. NVR shall support various face searching techniques: Museum search, search by image, search by track, and search by snapshot.
42. NVR shall support face match alarm/events.
43. NVR shall support storage of up to 10000 of faces.
44. NVR shall support various face statistics.
45. NVR shall support S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD).
46. NVR shall support plug-n-play via Speco's free P2P service.
47. NVR shall support DDNS capability via Speco's free DDNS service.
48. NVR shall auto-discover Speco's and other ONVIF Profile S compliant IP cameras on the local network without needing to locate the cameras manually.
49. NVR shall incorporate an embedded Linux® operating system using a proprietary software application for control, management and display.

C. Electrical Specification

1. Power Input 48VDC
2. Power Supply 48V Adapter with power cable
3. Power Consumption ≤ 5W (without HDD)
4. Power Cable USA standard (117 VAC, 3 prongs, 6 ft or 1.8 m)

D. Environmental Specification

1. Operating Temperatures -4° to 122°F (-10° to 50°C)
2. Operating Humidity 10% to 90%, non-condensing

E. Environmental Specification

1. Dimension 11.8"W x 9.8"D x 2.0"H
(300mm×248mm×52mm) (N8NRE)
15.0"W x 10.6"D x 2.0"H
(380mm×268mm×52mm) (N16NRE)
16.9"W x 17.8"D x 3.5"H

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition
N16NRE NVR with 8 Built-in PoE Ports and Face Recognition
N32NRE NVR with Face Recognition

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516
Fax. 1-631-957-3880
Web site: www.specotech.com

-
2. Mounting (430mm×453mm×89mm) (N32NRE)
Optional vented rack shelf

F. Mechanical Specification

1. System
 - a. Operating System: Embedded Linux
 - b. User Interface: Semi-transparent on-screen graphic overlays
2. Video
 - a. Inputs
8 IP cameras (N8NRE)
16 IP cameras (N16NRE)
32 IP cameras (N32NRE)
 - b. Outputs
HDMI, VGA
 - c. Encoding
H.264, H.265
 - d. Resolutions
8MP/5MP/4MP/3MP/1080P/720P
 - e. Frame Rate
30 fps
 - f. Pre-record
5 seconds
 - g. Post-record
10 minutes
 - h. Display Modes
1x1, 2x2, 3x3, 4x4, Custom
 - i. Outputs
1 x HDMI (4K), 1 x VGA
3. Audio
 - a. Network Inputs
32 IP
 - b. Inputs
1 x RCA
 - c. Outputs
1 x RCA
 - d. Codec
G.711A/G.711U
4. Network
 - a. WAN
1 x 1Gbps (RJ45) (N8NRE, N16MRE)
2 x 1Gbps (RJ45) (N32NRE)
 - b. Protocol
TCP/IP, DHCP, DNS, DDNS, UPnP, NTP,
SMTP, ONVIF Profile S
5. Simultaneous Playback
16 Channel Max
6. PTZ
Remote control/remote client
7. Alarms
 - a. Inputs
8
 - b. Outputs
4
8. Auxiliary
 - a. USB
1 x USB 2.0 Port (Front) (N8NRE, N16NRE, N32NRE)
1 x USB 2.0 Port (Rear) (N32NRE)
1 x USB 3.0 Port (Rear) (N8NRE, N16NRE, N32NRE)
9. Front Panel
 - a. Power Indicator
Power On, Blue
 - b. HDD Status
Recording, Blue

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition

N16NRE NVR with 8 Built-in PoE Ports and Face Recognition

N32NRE NVR with Face Recognition

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516

Fax. 1-631-957-3880

Web site: www.specotech.com

c. Network Indicator	Network access, Blue
10. User Interface	IR Remote, Mouse
11. Remote Control	Full remote control operation of PTZ
12. Remote Surveillance	
a. Web Viewer	MSIE
b. Control System	Speco Technologies SecureGuard
c. Mobile Devices	iOS, Android
13. Storage	1 x SATA (14TB max each HDD) (N8NRE) 2 x SATA (14TB max each HDD) (N16NRE) 8 x SATA (14TB max each HDD) (N32NRE)

Part 3 Execution

3.1 Examination

- A. Device shall be inspected for physical and cosmetic defects.
- B. Package box shall include device, power supply, mouse, remote control unit, installation and user guides on disk.

3.2 Preparation

- A. ESD-sensitive parts shall be properly protected against static buildup through the use of static shielding material.
- B. Package box shall contain adequate padding to prevent damage to device and parts during shipping.

3.3 Installation

- A. Device shall be installed in accordance with the manufacturers' installation guide provided.
- B. Device shall be installed by qualified service professionals.
- C. Device shall be installed in accordance with the National Electric Code or applicable local codes.
- D. Device shall be installed in locations which adequately supports the device's environmental and electrical requirements.

3.4 Field Quality Control

- A. Test for proper communication between device and supporting devices.
- B. Test for proper operation of device's system software and related software programs.

A&E Specification

N8NRE NVR with 4 Built-in PoE Ports and Face Recognition

N16NRE NVR with 8 Built-in PoE Ports and Face Recognition

N32NRE NVR with Face Recognition

Speco Technologies

200 New Highway, Amityville NY 11701

Tel. 1-800-645-5516

Fax. 1-631-957-3880

Web site: www.specotech.com

- C. Determine and report all problems to the manufacturers' customer service representatives.

3.5 Adjusting

- A. Make all necessary adjustments to the device and supporting devices to ensure the proper operation of the device.
- B. Make all necessary adjustments to the devices to satisfy end-user requirements.

3.6 Demonstration and Training

- A. Perform final inspection to validate and ensure proper functioning of device.