



2MP HD-TVI IR Motorized Dome Camera with Junction Box

VLD9M

2.8-12mm motorized lens, white housing

Features

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD, and 960H Analog
- IR Range: up to 98' (depending on scene reflection)
- True WDR (wide dynamic range)
- 12VDC Operation (power supply not included)
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included
- 5 year warranty
- NDAA Compliant*



Camera Specifications

Image Sensor	1/2.8" CMOS, 2MP
Minimum Illumination	Color: 0.001 lux @F1.2, (AGC ON); BW: 0 lux (IR ON)
Image Size	1920 x 1080
Video Output	AHD/TVI/CVI/CVBS
Image System	PAL/NTSC
Electronic Shutter	Auto: 1/25s - 1/50000s (PAL); 1/30s - 1/50000s (NTSC)
IR Distance	65.6ft - 98.4ft
Frame Rate	30fps (60Hz); 25fps (50Hz)
Lens Mount	D14
S/N Ratio	≥ 52dB (AGC OFF)

Functions

Function Control	OSD (COC Control)
Day & Night	Yes, Smart IR
WDR	Yes
DNR	3D DNR
AGC	Yes
Auto White Balance	Yes
Compensation	BLC
Sharpness	Yes
Mirror	Yes
Image Setting	Yes
Defect Correction	Auto
Angle Adjustment	Pan (0° - 345°); Tilt (0° - 77°); Rotation (0° - 345°)

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR OFF: < 1.5W; IR ON: < 5W
Operating Temperature	-22°F - 122°F
Operating Humidity	10% - 90% RH
Unit Dimensions	5.55" (Dia.) x 3.94" (L)
Unit Weight	1.81 lbs.

Optional Accessories



*Products are in compliance with NDAA Section 889 Part B Guidelines

