UL Rated 20-A:160-B:C



Description

When high-hazard fires demand fast response, one-person operation and exceptional performance, the wheeled dry chemical extinguisher is your best choice.

Its long-range discharge gives control over ordinarily out-of-reach fires and allows the operator to keep a safe distance from the fire source and smoke. Suitable for locations such as chemical and petroleum processing plants,



- Designed for single person operation
- 16" x 4" semipneumatic tires allow for easy mobility on any surface
- Far-reaching hose with 360° swivel joint
- Highly visible pressureindicating gauge
- Durable chromeplated brass valve. Cam-lever actuated
- Welded tubular-steel frame protects cylinder and valve
- Corrosion resistant red epoxy finish



At a Glance

warehouses



Model Proplus 50 MP

construction sites and

- Multipurpose Dry Chemical
- UL listed
- UL rated 20-A:160-B:C
 - DOT approved
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Product Specification

For use on the following types of fire:

| Net agent weight (Average) | 50 lb. |
|----------------------------|--------------|
| Unit weight (Average) | 140 lb. |
| Shell Diameter | 28.75 inches |
| Height | 46.25 inches |
| Discharge time | 36 seconds |
| Discharge range | 25-35 feet |
| Operating pressure | 240 psi |
| Cylinder | Steel |
| Valve | Brass |

