

Product Environmental Profile

On-Q metal enclosures with screw on cover



COMPANY OVERVIEW

• Sustainability built in to support our associates, customers, and the environment

At Legrand North America, we're committed to leading by example within our own operations, to developing high quality solutions for our customers' High Performance Buildings, and to transforming how people live and work – more safely, more comfortably, more efficiently.

• Better Performance

A core principle of designing for sustainability drives us to innovate products and systems that enable buildings to reach exceptional levels of performance, bringing about industry-leading ideas, inventions and initiatives.

• Better Operations

A commitment to a leadership role in operational excellence through environmental management, optimizing the way we manage energy, water and waste.

• Better Lives

A dedication to enhancing employee and community welfare through programs that help people enjoy healthier, more productive and more rewarding lives.

For more information on Legrand's PEPs and other sustainability initiatives, visit legrand.us/sustainability.



LEGRAND'S ENVIRONMENTAL COMMITMENTS

• Incorporate environmental management into our industrial sites

Of all Legrand sites worldwide, over 85% are ISO 14001 certified (sites belonging to Legrand for more than five years).

• Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.


• Involve the environment in product design

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

<p>Function</p>	<p>Supports structured wiring systems and wireless networking equipment surface or flush mounting with overall dimensions of 42.1" L x 14.3" W x 3.7" D (106.9cm x 36.3cm x 9.3cm). Enclosure includes two electrical knockouts on the bottom and three 2.5" (63.5mm) cable knockouts on top and protruded door. This product meets or exceeds the standards of UL 1863, UL 985, UL 1023 with lifetime of 20 years.</p>
<p>Reference Product</p>	<div style="text-align: center;">  </div> <p>Part Number: EN4200 On-Q Metal Enclosure EN4200</p>

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.

Product Environmental Profile

On-Q metal enclosures with screw on cover



PRODUCTS CONCERNED

The environmental data is representative of the following products:

EN2800
EN2000
EN1400



CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EC.

Total weight of Reference Product (with unit packaging)	333.62 oz (9458 g)
--	---------------------------

Plastics as % of weight		Metals as % of weight		Other as % of weight	
PE	0.4%	Steel	74.5%		
PVC	0.2%				
Other Plastic	<0.1%				
				Packaging as % of weight	
				paper (packaging)	24.7%
				PS (packaging)	0.3%
Total plastics	0.6%	Total metals	74.5%	Total other and packaging	24.9%

Estimated recycled material content: 28% of weight.



MANUFACTURING

The Reference Product comes from sites that have received ISO 14001 certification.



DISTRIBUTION

Products are distributed from logistics centers located to optimize transport efficiency using EPA SmartWay® certified carriers to reduce greenhouse gases emissions. Information on the distance of distribution is not available so the PCR hypothesis for "Intracontinental transport", 2175 miles (3500 km) by heavy truck, was used. This represents transportation of the Reference Product from our warehouse to the local point of distribution in the United States market.



Product Environmental Profile

On-Q metal enclosures with screw on cover



INSTALLATION

No electricity is required for installing the Reference Product.



USE

Servicing and maintenance:

Under normal conditions of use, this type of product requires no servicing or maintenance.

Consumable:

No consumables are necessary to use this type of product.



END OF LIFE

• Hazardous waste* contained in the product: no hazardous waste

(* Hazardous waste as defined by European Commission decision 2000/532/EC.

• Recycling rate:

Calculated using the method described in the IEC/TR 62635 technical report, the recyclability rate of the Reference Product is estimated as 100%. This value is based on data collected from a technological channel using industrial procedures. It does not pre-validate the effective use of this channel for end-of-life electrical and electronic products.

Separated into:	(% mass of Reference Product)
- plastic materials (excluding packaging):	1%
- metal materials (excluding packaging):	74%
- packaging (all types of materials):	25%



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use, and end of life. It is representative of products marketed and used in United States.

The following modelling elements were taken into account:

Manufacturing	Packaging taken into account. As required by the PEP ecopassport program, all transport for the manufacturing of the Reference Product, including materials and components, has been taken into account. The waste generated during manufacturing phase has been taken into account.
Distribution	Transport between the last distribution center and an average delivery to the sales area. The default scenario modelled maximizes the environmental impact.
Installation	The end of life of the packaging (3.23lb or 1467.42g) is taken into account at this phase. Transport of packaging to end of life treatment.
Use	<ul style="list-style-type: none"> • Under normal conditions of use, this type of product requires no servicing or maintenance. • No consumables are necessary to use this type of product. • Product category: enclosure. • Use scenario: no energy consumption during the 20 year working life. This modelling duration does not constitute a minimum durability requirement. • Energy model: Electricity(US)-2009
End of life	The default end of life scenario modelled maximizes the environmental impact.
Software used	EIME V5 and its database "CODDE-2015-04" and the indicators defined in the PCR ed 3 in alignment with the EN15804 standard

Product Environmental Profile

On-Q metal enclosures with screw on cover




ENVIRONMENTAL IMPACTS (continued)

	Total for Life cycle		Raw material and manufacturing		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
Global warming (GW)	3.40E+01	kgCO2 eq.	3.18E+01	93%	1.65E+00	5%	1.48E-01	< 1%	0.00E+00	0%	4.59E-01	1%
Ozone depletion (OD)	3.67E-07	kgCFC-11 eq.	3.59E-07	98%	3.34E-09	< 1%	1.06E-09	< 1%	0.00E+00	0%	3.07E-09	< 1%
Acidification of soil and water (A)	1.01E-01	kgSO2 eq.	9.14E-02	90%	7.40E-03	7%	7.21E-04	< 1%	0.00E+00	0%	1.94E-03	2%
Water eutrophication (WE)	1.97E-02	kg(P04)3- eq.	1.39E-02	71%	1.70E-03	9%	7.78E-04	4%	0.00E+00	0%	3.23E-03	16%
Photochemical ozone creation (POCP)	1.24E-02	kgC2H4 eq.	1.17E-02	94%	5.26E-04	4%	5.10E-05	< 1%	0.00E+00	0%	1.46E-04	1%
Depletion of abiotic resources - elements (ADPe)	1.52E-05	kgSb eq.	1.51E-05	99%	6.59E-08	< 1%	6.48E-09	< 1%	0.00E+00	0%	1.94E-08	< 1%
Total use of primary energy (PE)	1.23E+03	MJ	1.20E+03	98%	2.21E+01	2%	1.94E+00	< 1%	0.00E+00	0%	5.48E+00	< 1%
Net use of fresh water (FW)	3.36E-01	m3	3.36E-01	100%	1.47E-04	< 1%	4.78E-05	< 1%	0.00E+00	0%	1.22E-04	< 1%
Depletion of abiotic resources - fossil fuels (ADPf)	3.66E+02	MJ	3.35E+02	91%	2.32E+01	6%	2.06E+00	< 1%	0.00E+00	0%	6.04E+00	2%
Water pollution (WP)	2.50E+03	m3	2.14E+03	86%	2.71E+02	11%	2.27E+01	< 1%	0.00E+00	0%	6.54E+01	3%
Air pollution (AP)	4.48E+03	m3	4.37E+03	97%	6.75E+01	2%	1.86E+01	< 1%	0.00E+00	0%	2.64E+01	< 1%

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website. The environmental impacts of the Reference Product are representative of the products covered by the PEP, which therefore constitute a homogeneous environmental family.

% ENVIRONMENTAL IMPACT PER LIFECYCLE STAGE OF REFERENCE PRODUCT



The environmental impact of the Reference Product occurs predominantly during the manufacturing and Distribution phase.

Product Environmental Profile

On-Q metal enclosures with screw on cover



ENVIRONMENTAL IMPACTS (continued)

For products other than the Reference Product, the environmental impacts can be estimated by weighting the environmental impacts of the Reference Product by the values shown in the table below. Impacts for manufacturing are proportional to the mass of the reference product. For products sold in the European market, apply the variable 'E' to the values shown for distribution. This represents international transportation of 19000km by boat and 1000km by truck. Impacts for Installation, Use and End of Life are the same as the Reference Product.

Part Number	Manufacturing
EN4200	1.0
EN2800	ADPe : 0.9 all else : 0.8
EN2000	ADPe : 0.9 all else : 0.6
EN1400	ADPe : 0.9 all else : 0.4

Distribution in Europe (E)
A : 10.8 AP : 5.7 EP : 4.6 POCP : 7.5 all else : 1.5

Registration number: LGRP-00703-V01.01-EN	Drafting rules: "PCR-ed3-EN-2015 04" Supplemented by "PSR-0005-ed1-EN-2012 12 11"
Verifier's accreditation number: VH26	Information and reference documents: www.pep-ecopassport.org
Date of issue: 03-2018	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025:2010 Internal <input type="checkbox"/> External <input checked="" type="checkbox"/>	
The PCR Review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN).	
PEP are compliant with XP C08-100-1 :2014 The elements of the present PEP cannot be compared with elements from another program.	
Document in compliance with ISO 14025:2010: "Environmental labels and declarations - Type III environmental declarations"	
In compliance with ISO 14040:2006: "Environmental management - LCA - Principles and framework" In compliance with ISO 14044:2006: "Environmental management - LCA - Requirements and guidelines" In alignment with EN 15804:2012+A1:2013: "Sustainability of construction works - EPD's - Core rules for the product category of construction products"	