

Technical Data Sheet



NJ210BKWH1000

2 Conductor 10AWG Unjacketed THHN 600V

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	10
• Conductor Stranding	65x28
• Conductor Type	Bare copper
• Nominal DCR	1.1 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thickness	0.020 in - .005"
• Insulation Color Code	1. Black 2.White or 1.Black. 2. Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Unjacketed
Jacket Thickness	--
Nominal Cable O.D.	0.326 in
Plenum	No
NEC UL Rating	THHN THWN
RoHS Compliant	Yes
Pull Tension	220 lbs
Bend Radius	2.87 in
Cable Weight	76 lbs
OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-25 to 90 Deg C - Dry (THHN), -25 to 75 Deg C - Wet (THWN)
UL Voltage Rating	600

Products:	
NJ210BKWH1000	Black/ White - 1000ft put up
NJ210BKRD1000	Black/ Red - 1000ft put up

MOQ: 12,000ft

2833 West Chestnut Street-Washington, PA 15301 | 800-245-4964 | www.westpennwire.com