



256100

RG6/U CCS CATV Dual Shield Plenum
CATV/MATV DBS

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Copper Covered Steel -CCS
• Nominal DCR	28 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam FEP
• Insulation Thickness	0.17 in
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Shield Type 2	Aluminum Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	75 Ohm
• Nom. Cap. Between Conductors	16.2 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Nominal Cable O.D.	0.237 in
Plenum	Yes
NEC UL Rating	CATVP
RoHS Compliant	Yes
Pull Tension	70 lbs
Bend Radius	2.37 in
Cable Weight	29 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	82 %
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300



256100

RG6/U CCS CATV Dual Shield Plenum

Attenuation

FREQUENCY (MHz)	ATTENUATION (db/100ft)
5 MHz	0.45 dB
55 MHz	1.6 dB
100 MHz	2 dB
270 MHz	2.9 dB
400 MHz	4.5 dB
540 MHz	4.9 dB
750 MHz	6.6 dB
1000 MHz	8 dB
1450 MHz	10.3 dB
2250 MHz	13.36 dB
3000 MHz	15.42 dB

Related Products

RELATED PRODUCTS	
Non Plenum Number	6100
"F" Type Crimp	CN-F56TFE
"F" Type Compression	CN-F6MCV