



Protect a high speed network from noise and electromagnetic interference when connecting with our Snagless Shielded Cat6 patch cable. For voice/data/video distribution, this cable will handle bandwidth-intensive applications and drastically reduces both impedance and structural return loss (SRL). Each patch cable is fully tested to meet ANSI/TIA 568 C.2 Cat6 component requirements. Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality cable and plugs, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code a network installation. Individual length label on each cable for ease of use.

## Features & Benefits

Designed for network adapters, hubs, switches,<br/>routers, HDBaseT applications and moreSupports 10 Gigabit networks up to 180ft for fast data transmission and<br/>maximum performance and supports 1 Gigabit up to 328ftMeets the ANSI/TIA-568-C.2 Cat6 requirements for<br/>supporting a wide variety of applicationsConstructed with shielded twisted pair (STP) wires, designed to protect a<br/>high speed network from noise and electromagnetic interference

Snagless connector design for high density

environments and protecting the RJ-45 connector's Available in a variety of colors to color-code a network lock

## Specifications

## General Info

Product Line	C2G	Color	White
UPC Number	757120009160	Country Of Origin	Vietnam
Features	PoE (Power Over Ethernet)	Application Sector	Residential, Commercial, Industrial
Туре	Cable		
Dimensions			
Cable Length	3 ft		
Additional Information			

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG
Cable Type	Ethernet Patch Cable, Booted, Snagless, Shielded (STP)	Jacket Rating	Standard / Non- Rated
Adapter Rear	RJ-45 Male	Adapter Front	RJ-45 Male