



## 454

22/2 Bonded Shield CMR

Line Level Audio Note: Shield Bonded to the Jacket for easy stripping

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	1
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Tinned Copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	Bonded Overall 100% Aluminum Foil
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	22 AWG
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	45 Ohm
• Nom. Cap. Between Conductors	34 pF/ft
• Nom. Cap. Conductor to Shield	67 pF/ft

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.02 in
Nominal Cable O.D.	0.135 in
Plenum	No
NEC UL Rating	CMR
RoHS Compliant	Yes
Pull Tension	28 lbs
Bend Radius	1.215 in
Cable Weight	15 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	66 %
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



**454**

22/2 Bonded Shield CMR

**Related Products**

RELATED PRODUCTS	-
Plenum Number	D25454
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231