Product data sheet Characteristics

AP9562 Rack PDU, Basic, 1U, 15A, 120V, (10)5-15





Overview

Lead time	Usually in Stock	
-----------	------------------	--



Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	12 ft (3.7 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets

Complementary

- Compression of the compression		
Input Voltage	100 V	
	120 V	
Height	1.7 in (4.4 cm)	
Width	17.6 in (44.7 cm)	
Output Voltage	120 V	
Depth	2.2 in (5.7 cm)	
Net Weight	5.5 lb(US) (2.5 kg)	
Mounting location	Front	
	Rear	
Mounting preference	No preference	
Input Plug Type	NEMA 5-15P	
Mounting Mode	Rack-mounted	
Rack units	1U	
Mounting position	Horizontal	
Line Rated Current	12 A	
Input current limits	15 A	
Load Capacity	1400 VA	
Input Frequency	50/60 Hz	
Outlet type and quantity	10 NEMA 5-15R	

Environment

Product Certifications	cUL Listed[RETURN]METI Denan[RETURN]UL Listed
Ambient Air Temperature for Operation	23113 °F (-545 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304203865
Returnability	No
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7 cm)
Package 1 Width	9.02 in (22.9 cm)
Package 1 Length	18.3 in (46.4 cm)
Package 1 Weight	8.02 lb(US) (3.64 kg)
1 ackage 1 Weight	0.02 Ib(00) (0.04 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace