LC-LC 62.5/125µm OM1 MM Duplex Fiber Optic Jumper



Package Includes

- A. LC-LC 62.5/125µm OM1 MM Duplex Fiber Jumper, 1 pc.
- B. Test Results Label, 1 pc.

Features and Benefits


- Made from OFNR riser rated cables, exceeding industry requirements Used with ICC fiber optic products
 Available in 1, 2, 3, 5, 7, and 10 meters
 Dust Caps included

- Test results included



Page 1 of 2





NOTE: UNLESS OTHERWISE SPECIFIED

1. Cable:

A. Color: Orange

B. Fiber Counts: 2 Fiber Zipcord

C. Fiber Type: Multimode 62.5/125µm

D. Attenuation: 2.9/0.6 dB/km @ 850/1300 nm E. Bandwidth: 220 MHz.km EMB @ 850 nm

F. Cable Data:

• Cable diameter: .079 in (2.0mm)

Weight: 12 lbs./kft
Bend radius: 1.2" MIN
Loading: 135 lbs. MAX

Impact cycle: 1500

2. LC Connector:

A. Ferrule: Zirconia

B. Insertion Loss: 0.2 dB Typical, 0.3 dB MAX

C. Reflection: N/A

3. Compliance:

A. ANSI/TIA-568-C.3

4. Length: XX: 01, 02, 03, 05, 07, & 10

| ITEM NUMBER | L (LENGTH) |
|-------------|------------------|
| ICFOJ1M301 | 1 METER ± 10 CM |
| ICFOJ1M302 | 2 METER ± 10 CM |
| ICFOJ1M303 | 3 METER ± 10 CM |
| ICFOJ1M305 | 5 METER ± 10 CM |
| ICFOJ1M307 | 7 METER ± 10 CM |
| ICFOJ1M310 | 10 METER ± 10 CM |

Part No: ICFOJ1M3XX

Rev: A Page 2 of 2 888-ASK-4ICC icc.com csr@icc.com

