



**Product:** [FXU Cassette OM4 12P MPO12\(F\)](#)

FX Ultra Cassette OM4 12 Ports MPO-12 (F)

**Product Description**

FX Ultra Cassette OM4 12 Ports MPO-12 Female. Available in several adapter colors.

**Technical Specifications**

**Product Overview**

Environmental Space:	Indoor
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers

**Construction**

**Fiber Cable Construction**

Fiber Type	OM4
Weight:	0.441 lbs
Height:	1.5 in
Width:	4.5 in
Length:	6.6 in

**Mechanical Characteristics**

Front Connection:	1 Inch Pullout
-------------------	----------------

**Temperature Range**

Operating Temp Range:	-10 to 60°C
Storage Temp Range:	-10 to 75°C

**Product Material**

**Materials**

Element	Description	Material	Color
Zirconia-Ceramic	Adapter Sleeve Material	Zirconia-Ceramic	
Plastic - UL94V-0	Front Connector Body	Plastic - UL94V-0	Erika Violet
Plastic - UL94V-0	Cassette Assembly	Plastic - UL94V-0	Black

**Standards**

MII Order #39 (China RoHS):	EUP 50
-----------------------------	--------

**Part Number**

Related Parts:	FX UHD & FXU Patch Panels, FX MPO Trunks
----------------	--

**Variants**

Item #	Color	Connector Type	Polarity Identification
FC4U12LDMFAA	Erika Violet	LC Duplex	Type-A
FC4U12LDMF1E	Erika Violet	LC Duplex	Type-A Alternate
FC4U12LDMF1A	Erika Violet	LC Duplex	Type-A Alternate

FC4U12LDMF	Erika Violet	LC Duplex	Type-A
------------	--------------	-----------	--------

## Product Notes

Packaging:	Individually packaged in a plastic shell, Shipped in cardboard box (14/box)
------------	---

## History

Update and Revision:	Revision Number: 0.106 Revision Date: 08-27-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.