



6310

RG6/U BC Quad Shield CATV/MATV Outdoor
CATV/MATV DBS

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Copper Covered Steel -CCS
• Nominal DCR	28 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam Polyethylene
• Insulation Thickness	0.18 in
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil + Aluminum Braid
• Shield Type 2	Overall 100% Aluminum Foil + Aluminum Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	75 Ohm
• Nom. Cap. Between Conductors	16.2 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PE
Nominal Cable O.D.	0.295 in
Plenum	No
NEC UL Rating	Outdoor
Pull Tension	85 lbs
Bend Radius	2.94 in
Cable Weight	31 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	82 %
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



6310

RG6/U BC Quad Shield CATV/MATV Outdoor
CATV/MATV DBS

Attenuation

FREQUENCY (MHz)	ATTENUATION (db/100ft)
5 MHz	0.57 dB
55 MHz	1.45 dB
100 MHz	1.85 dB
270 MHz	3.07 dB
400 MHz	3.85 dB
540 MHz	4.6 dB
750 MHz	5.4 dB
1000 MHz	6.3 dB
1450 MHz	8.05 dB
2250 MHz	9.99 dB
3000 MHz	11.9 dB

Related Products

RELATED PRODUCTS	
"F" Type Crimp	CN-F56ALX
"F" Type Compression	CN-F6MCV