



Product: [CAT6A UTP CM Patch Cords](#)

DataConnect CAT6A UTP Patch Cords 24 AWG, CM

Product Description

DataConnect CAT6A UTP 24 AWG CM Non-Bonded Patch Cords

Technical Specifications

Product Overview

Suitable Applications:	Ethernet 10/ 100/ 1000BASE-T, 2.5G/ 5G/ 10GBASE-T
------------------------	---

Physical Characteristics (Overall)

Total Number of Pairs:	4
Overall Nominal Diameter:	0.264 in
Wiring Scheme:	T568A/B-T568A/B
Packaging:	Individually packaged in a clear plastic bag.

Connectors

Materials

Description	Material	Color
Boot	transparent - PVC	Translucent
Conductor	BC - Bare Copper	
Front Connection	Blades Phosphor Bronze with 50u inch Gold over Nickel Plating	
Insulation	HDPE (CMI-75E)	
Outer Jacket	PVC - Polyvinyl Chloride	

Electrical Characteristics

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm

Temperature Range

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C

Mechanical Characteristics

Min Bend Radius (Overall Cable):	1.040 in
Plug /Jack Compatibility:	RJ45

Termination Interface

Connection	Durabilities
Mated Connection	750 Cycles

Standards

UL Rating:	CM (Not Riser or Plenum)
ISO/IEC Compliance:	IEC 60603-7
Data Category:	Category 6A
TIA/EIA Compliance:	Category 6A - TIA 568.2-D, ISO/IEC 11801-1
IEEE Compliance:	IEEE 802.3at type 1 and 2 (PoE) up to 30W, IEEE 802.3bt type 3 and 4 (PoE) up to 100W, CISCO (UPOE) up to 60W, Power over HDBaseTTM (POH) up to 100W

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	c(UL)us Listed, UL 1863, UL File E77103
-----------------	---

Related Part Numbers

Related Parts:	DataConnect CAT6A Modular Jacks, DataConnect CAT6A Patch Panels
----------------	---

Variants

Item #	Color	Length
CA43100003	Black	3 ft
CA43100005	Black	5 ft
CA43100007	Black	7 ft
CA43100010	Black	10 ft
CA43100015	Black	15 ft
CA43106002	Blue	2 ft
CA43106003	Blue	3 ft
CA43106004	Blue	4 ft
CA43106005	Blue	5 ft
CA43106006	Blue	6 ft
CA43106007	Blue	7 ft
CA43106010	Blue	10 ft
CA43106015	Blue	15 ft
CA43108003	Gray	3 ft
CA43108005	Gray	5 ft
CA43108007	Gray	7 ft
CA43108010	Gray	10 ft
CA43108015	Gray	15 ft
CA43105003	Green	3 ft
CA43105005	Green	5 ft
CA43105007	Green	7 ft
CA43105010	Green	10 ft
CA43105015	Green	15 ft
CA43103003	Orange	3 ft
CA43103005	Orange	5 ft
CA43103007	Orange	7 ft
CA43103010	Orange	10 ft
CA43103015	Orange	15 ft
CA43109002	White	2 ft
CA43109003	White	3 ft
CA43109004	White	4 ft
CA43109005	White	5 ft
CA43109006	White	6 ft
CA43109007	White	7 ft
CA43109010	White	10 ft
CA43109015	White	15 ft
CA43104002	Yellow	2 ft
CA43104003	Yellow	3 ft
CA43104004	Yellow	4 ft
CA43104005	Yellow	5 ft
CA43104006	Yellow	6 ft
CA43104007	Yellow	7 ft

CA43104010	Yellow	10 ft
CA43104015	Yellow	15 ft

Product Notes

Labeling:	Belden Part Number, Performance Acronym, Wiring Scheme and Cord Length.
-----------	---

History

Update and Revision:	Revision Number: 0.8 Revision Date: 02-26-2024
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.