



**221**

22/2 Unshielded CMR

Audio and Control

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
• Cabling Lay Length	1.5 in
• Twists/Foot	8 twist/ft
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Insulation Thickness	0.007 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.12 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	18 lbs
Bend Radius	1.08 in
Cable Weight	12 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

**Related Products**

RELATED PRODUCTS	-
Plenum Number	25221B