



**274**

22/15 Unshielded CMR  
Audio and Control

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	15
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Insulation Thickness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green,5. Brown,6.Blue,7.Orange,8.Yellow,9.Purple,10.Gray,11.Pink,12.Tan,13.WH-BK, 14.WH-RD, 15.WH-GN
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.251 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	135 lbs
Bend Radius	2.259 in
Cable Weight	58 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



**274**

22/15 Unshielded CMR  
Audio and Control

**Related Products**

RELATED PRODUCTS	-
Plenum Number	25274B