



Pass and Seymour
15A 120V/125V Combination Single-Pole Toggle Switch and Single Receptacle, Light Almond
Part No. 691LA

Our standard Pass and Seymour combination switches allow you to add lights to any room in your home without having to add or replace wall boxes.



Features & Benefits

Easily accessible break-off separate or common feed.

Two devices fit into the space of one.

Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

One-piece heat-treated triple-wipe brass power contacts.

Grounding combination devices meet NEC Requirements.

Specifications

General Info

| | | | |
|--------------------|------------------------|-----------------------|--------------|
| Product Line | Pass & Seymour | Color | Light Almond |
| Finish | Matte | UPC Number | 785007691054 |
| Country Of Origin | Mexico | Number of Receptacles | 1 |
| Outlet Type | Indoor | Package Quantity | 1 |
| Application Sector | Residential/Commercial | Standard | UL20, UL498 |
| Type | Combination | | |

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140597 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Technical Information

| | | | |
|--------------------------|-----------------------|-----------------------|---------------------|
| Is Tamper-Resistant | No | Contact Configuration | N-0 |
| Operating Cycles | 30000 | Actuator | Toggle |
| Connection | Side wire | Contact Rating | 15 Amp, 120/125 VAC |
| Amperage | 15 A | Number of Poles | Single Pole |
| Is Weather Resistant | No | Indoor/Outdoor | Indoor |
| NEMA Configuration Code | 5-15R | Supply Voltage | 125 |
| Voltage | 120 V | Connection Type | Wired |
| Environmental Conditions | Flammability: UL94 V2 | | |
