



1110

RG11/U 14AWG CATV Flooded Burial Outdoor
CATV/MATV DBS

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	14
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	2.6 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam Polyethylene
• Insulation Thickness	0.28 in
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Shield Type 2	Aluminum Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	75 Ohm
• Nom. Cap. Between Conductors	16.2 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PE
Jacket Thickness	0.044 in
Nominal Cable O.D.	0.405 in
Plenum	No
NEC UL Rating	Outdoor
Pull Tension	150 lbs
Bend Radius	3.645 in
Cable Weight	65 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	82 %
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



1110

RG11/U 14AWG CATV Flooded Burial Outdoor
CATV/MATV DBS

Attenuation

FREQUENCY (MHz)	ATTENUATION (db/100ft)
5 MHz	0.38 dB
55 MHz	0.92 db dB
100 MHz	1.2 dB
270 MHz	1.92 dB
400 MHz	2.4 dB
540 MHz	2.85 dB
750 MHz	3.4 dB
1000 MHz	4.05 dB
1450 MHz	5.05 dB
2250 MHz	6.42 dB
3000 MHz	7.46 dB

Related Products

RELATED PRODUCTS	
"F" Type Crimp	CN-F11ALX
"F" Type Compression	CN-FS11V