

Opt-X® Fiber Cleaver

APPLICATION

The Opt-X Fiber Cleaver provides high precision at a low cost. This compact and easy to use cleaver is perfect for all cleaving applications, from fusion splicing to mechanical splicing, and is ideal for working with Leviton FastCAM® connectors. For a self-contained workspace, mount the cleaver to the optional work tray and use the optional gooseneck LED for task lighting.

The Opt-X Fiber Cleaver can be purchased individually or as part of the FastCAM Tool Kit, which includes the cleaver, lint free dry wipes, alcohol pads, and a jacket stripper.



SPECIFICATION

Cleaver shall work with both 250 µm coated and 900 µm buffered fibers. It shall guarantee a cleave angle of 90° +/- 0.5°, and the 16-position blade shall have a blade life of approximately 48,000 cleaves.

COUNTRY OF ORIGIN

Korea

WARRANTY INFORMATION

For a copy of Leviton product warranties, visit www.leviton.com/warranty.

Page 1 of 1

D14 4875

Leviton Network Solutions

2222 - 222nd St. SE
 Bothell, WA 98021-4416

tel 1-800-824-3005
 tel +1-425-486-2222
 appeng@leviton.com
www.leviton.com

Asia / Pacific

T +1.631.812.6228
 E infoasean@leviton.com

Europe

T +33.6.8869.1380
 E infoeurope@leviton.com

Canada

T +1.514.954.1840
 E pcservice@leviton.com

India / SAARC

T +91.80.4322.5678
 E infoindia@leviton.com

Caribbean

T +1.954.593.1896
 E infocaribbean@leviton.com

Mexico

T +52.55.5082.1040
 E lsamarketing@leviton.com

China

T +852.2774.9876
 E infochina@leviton.com

Middle East & Africa

T +971.4.886.4722
 E lmeinfo@leviton.com

Colombia

T +57.1.743.6045
 E infocolombia@leviton.com

South Korea

T +82.2.3273.9963
 E infokorea@leviton.com

FEATURES

- High precision cleaves
- 250 µm coated or 900 µm buffer fiber
- Single-mode or multimode use
- 16-position rotatable and replaceable blade
- 3-action operation

DESIGN CONSIDERATIONS

- Compact, ergonomic design
- Optional work tray and gooseneck LED for task lighting available

SPECIFICATIONS

Fiber Diameter	125 µm
Coating Diameter	250 µm ~ 900 µm
Cleave Angle	90° ± 0.5°
Cleave Length	5 ~ 20 mm
Blade Lifetime	48,000 cleaves (3,000 per blade position)
Cleaver Dimensions	58 x 55 x 48 mm
Weight	360 g

PART NUMBERS

Description	Part No.
FastCAM® Tool Kit with Opt-X Fiber Cleaver, Stripper, and Consumables	49800-MSK
FastCAM® Tool Kit with Opt-X Fiber Cleaver, Stripper, Work Tray, Gooseneck LED, and Consumables	49800-LAK
Opt-X Cleaver	49886-LNX
Gooseneck LED	49886-LGN
Work Tray	49886-LNT