



C210

2 Conductor 10AWG Unshielded Outdoor TC
Large Venue Speaker Distribution

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	10
• Conductor Stranding	65x28
• Conductor Type	Bare copper
• Nominal DCR	1.1 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thickness	0.025 in
• Insulation Color Code	1. Black 2.White
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.047 in
Nominal Cable O.D.	0.357 in
Plenum	No
NEC UL Rating	TC
RoHS Compliant	Yes
Pull Tension	235 lbs
Bend Radius	3.213 in
Cable Weight	80 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	600



C210

2 Conductor 10AWG Unshielded Outdoor TC
Large Venue Speaker Distribution

Related Products

RELATED PRODUCTS	-
Plenum Number	25210