



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|------------------------------------|
| Main Input Voltage | 120 V |
| Main Output Voltage | 120 V |
| Kw Rating | 330 W |
| Rated power in VA | 600 VA |
| Product or Component Type | Uninterruptible power supply (UPS) |
| Input Connection Type | NEMA 5-15P |
| Output connection type | 5 NEMA 5-15R 2 NEMA 5-15R surge |
| Cable length | 5 ft (1.5 m) |
| Battery Type | Lead-Acid battery |
| Provided equipment | User Manual |

Batteries & Runtime

| | |
|------------------------------|-----------------------------------|
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| Typical recharge time | 10 h |
| RBC Quantity | 1 |
| Battery Charge Power (Watts) | 7 W rated |
| Battery power in VAh | 78 VAh capacity 66 VAh runtime |
| Battery Life | 3...5 year(s) |
| Extendable Run Time | 0 |

General

| | |
|-------------------------------------|----|
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|-----------------------|
| Height | 5.5 in (13.9 cm) |
| Width | 10.79 in (27.4 cm) |
| Depth | 4.1 in (10.5 cm) |
| Net Weight | 7.69 lb(US) (3.49 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | No |

Input

| | |
|-------------------------|--------------------------------|
| Input Frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Efficiency at full load | 92...139 V |

Output

| | |
|----------------------------------|--------------------------------------|
| Max Configurable Power (Watts) | 330 W |
| Output Frequency (sync to mains) | 50/60 Hz +/- 3 Hz sync to mains |
| Topology | Standby |
| Wave type | Stepped approximation to a sine wave |
| Maximum configurable power in VA | 600 VA |
| Transfer Time | 6ms typical : 10ms maximum |

Conformance

| | |
|-----------------------------|---|
| Product Certifications | California (CEC) Battery Charger[RETURN]cTUVus[RETURN]NOM |
| Equipment protection policy | Lifetime : \$75000 |

Environmental

| | |
|---------------------------------------|--|
| Ambient Air Temperature for Operation | 32.0000000000...104.0000000000 °F (0...40 °C) |
| Relative Humidity | 0...90 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | 5.0000000000...113.0000000000 °F (-15...45 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |
| Acoustic level | 35 dBA |
| Heat dissipation | 16 Btu/h |

Communications & Management

| | |
|---------------|--|
| Control panel | LED status display with on line : on battery : replace battery and overload indicators |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|----------------------------|--|
| Surge energy rating | 490 J |
| Filtering | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m |
| Let Through Voltage Rating | 5 V |

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| GTIN | 731304325116 |
| Returnability | No |

Packing Units

| | |
|------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.7 in (19.6 cm) |
| Package 1 Width | 6.6 in (16.8 cm) |
| Package 1 Length | 14.3 in (36.3 cm) |
| Package 1 Weight | 8.40 lb(US) (3.81 kg) |
| SCC14 | 10731304325113 |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|