AP9810 APC Dry Contact I/O Accessory







Overview

Presentation	UPS management accessory that provides two dry contact input and one relay output interface to APC UPS management offers with UIO ports such as the UPS Network Management Card (AP9641, AP9643) or Dry Contact I/O SmartSlot Card (AP9613).
Lead time	Usually in Stock

Main

Provided Equipment Cat 5 ethernet cable User Manual

Physical

•		
Color	Black	
Height	0.87 in (2.2 cm)	
Width	1.78 in (4.52 cm)	_
Depth	1.76 in (4.46 cm)	
Net Weight	0.11 lb(US) (0.05 kg)	_
Mounting preference	No preference	
Mounting Mode	Not rack-mountable	

Conformance

Comomanco		
Standards	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-6	

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Operating altitude	03333 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	5149 °F (-1565 °C)
Storage altitude	015000 ft (0.004572.00 m)
Storage Relative Humidity	095 %

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304274032	
Returnability	No	
Country of origin	PH	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.30 in (3.300 cm)
Package 1 Width	10.00 in (25.400 cm)
Package 1 Length	5.00 in (12.700 cm)
Package 1 Weight	4.94 oz (140.000 g)
Unit Type of Package 2	PAM
Number of Units in Package 2	576
Package 2 Height	48.43 in (123.000 cm)
Package 2 Width	47.24 in (120.000 cm)
Package 2 Length	39.37 in (100.000 cm)
Package 2 Weight	178.49 lb(US) (80.960 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace	