



A high quality BNC cable for video applications including CCTV, broadcast, studio, boardroom presentations, home theater, etc. Manufactured from 75 Ohm RG59/U dual shield coax cable (60% copper braid over foil) with a 22 AWG copper-covered steel center conductor. Finished with bright nickel-plated BNC connectors that have molded PVC strain relief to protect the cable from wear over time.

## Features & Benefits

RG59/U Dual Shield coaxial cable

Constructed with a 75copper conductor

Nickel-plated BNC connectors

Molded PVC strain relief

## Specifications

### General Info

|                    |                                     |                   |       |
|--------------------|-------------------------------------|-------------------|-------|
| Product Line       | C2G                                 | Color             | Black |
| UPC Number         | 757120400325                        | Country Of Origin | China |
| Application Sector | Residential, Commercial, Industrial | Type              | Cable |

### Dimensions

|              |        |
|--------------|--------|
| Cable Length | 100 ft |
|--------------|--------|

### Additional Information

|                          |     |                          |                              |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

### Technical Information

|                 |                          |               |                      |
|-----------------|--------------------------|---------------|----------------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge    | 22 AWG               |
| Cable Type      | Video                    | Jacket Rating | Standard / Non-Rated |

---

Adapter Rear

BNC Male

Adapter Front

BNC Male

---