HUBBELL
Premise Wiring

PlugTrak, Aluminum, Tamper Resistant, 20A Circuit, 5 Receptacle, 5′ Aluminum

By Hubbell Premise Wiring
Catalog # HBLALU24GB512

PlugTrak, Aluminum, Tamper Resistant, 20A Circuit, 5 Receptacle, 5′ Aluminum

Features

- Multiple spacing configurations
- Satin anodized scratch resistant finish
- Hubbell designed and manufactured single receptacle
- Insulation displacement wiring provides superior wire retention

General

Catalog Number	HBLALU24GB512
EU RoHS Indicator	Contact Manufacturer
Item Type	Aluminum Pre-Wired PlugTrak
Number of Receptacles	5
Performance	• Electrical - Receptacle Rating - NEMA 5-15R and NEMA 5-20R • Mechanical - Wire - #12 AWG Stranded Copper
Series	Aluminum
Style	Standard
Type	Single Circuit
UPC	783585113364

Dimensions

Length	5 ft

Electrical Ratings

Current / Amperage Rating	15 A
Voltage Rating	125 VAC

Conductor Related

Wire Size	#12 AWG THHN

Certifications And Compliance

Industry Standard(s)	• CSA Standard C22.2 no. 62 • E253976 /E253830 /E253833 • UL Standard UL 5

Logistics

Carton Quantity	2

Product Assets

Catalog Page - PREM U52 CatalogPage
Catalog Page - WDK S-36 Catalog Page
Catalog Page - PREM U37 CatalogPage
Catalog Page - WDK S-51 Catalog Page
Catalogs - WDK Catalog Full 2024
Catalogs - Premise Wiring Catalog

©2024 Hubbell Incorporated. All rights reserved.