

netSELECT  
Jacks  
Category 6A Jack

# HUBBELL

## Features

- Cost effective solution supporting IEEE 802.3 10Gbe applications
- Fast, Reliable Cobra-Lock termination with no punchdowns or special tools
- Supports POE, tested above the IEEE 802.3bt 4PPoE Standard
- UL 2043 Listed for use in plenum (air handling) spaces
- Universal wiring label - one jack for T568A or T568B wiring

## Ordering Information

Description	Color	Catalog Number	UPC
netSELECT Category 6A Jack, Universal TIA568A/B Wired, Light Almond/Office White	Light Almond/Office White	NSJU6ALA	883778507359



## Listings

ANSI/TIA-568.2-D Category 6A channel requirements  
cULus Listed 1863  
UL 2043  
RoHS Compliant

## Specifications

Housing Material	High-impact thermoplastic (UL 94V-0)
Nose Contacts	Copper Alloy with Gold Over Plating
Dimensions In (mm) (H x W x D)	0.87 (22) x 0.67 ( 17) x 1.39 ( 35)
Conductor Compatibility	24-22 AWG Solid
IDC Re-Termination Cycles	25

## Performance

### Application

10BASE-T through 10GBASE-T Ethernet

### Electrical Performance

TIA 568 CAT6A Channel Compliant

### Plug Mating Cycles

750 Minimum

### PoE Support

IEEE 802.3af, 802.3at,  
802.3bt Type 3 and Type 4

## Accessories

netSELECT 24 Port Unloaded Panel	NSPJ24
netSELECT 48 Port Panel, Unloaded	NSPJ48
CAT6A Reduced Diameter Plenum Cable, Blue	C6ASPDSB
CAT6A Field Termination Plug	SP6A
CAT6A MPTL Assembly w/ 18" Lead	SCP6A

## Online Resources

Customer Sales Drawings  
eCatalog  
Installation Instructions

