



Fiber Optic Adapter Panel, H4 Opening, 6 MTP Simplex, Aqua

By Hubbell Premise Wiring
Catalog # [FSPMTPH4AQ6](#)

Fiber Optic, Adapter Panel, H4 Opening, 6 MTP Simplex, Aqua.



Application

Interconnect

General

Color	Aqua
Environmental Conditions	Indoor
Item Type	MPO
Material	Ceramic Zirconium
Material - Mounting Hardware	Snap-In
Performance	<ul style="list-style-type: none">Optical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical)Environmental - Operating temperature - 0 °C to +75 °C
Sub Brand	OptiChannel
UPC	662620605456

Electrical Ratings

Insertion Loss 0.30 dB

Conductor Related

Fiber Size 125 Micron

Certifications and Compliance

Industry Standard(s)

- TIA-568-C.3
- TIA-604-FOCIS

Logistics

Carton Quantity 4

Product Assets

[Sales Drawings - HPW_FSPMTPH4_DRAWING_PDF](#)
[Sell Sheets - H4 4 Across Rack Enclosures](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
PREM-FSPMTPH4AQ6-SPEC-EN | REV 1/2024