

## Micro USB to USB OTG Host Adapter Cable, 5-Pin Micro USB B to USB A M/F, 6-in.

## MODEL NUMBER: U052-06N





Connect a USB OTG ready Tablet or Smartphone to USB 2.0 Devices

### Description

Tripp Lite U052-06N, USB OTG Adapter, is the perfect solution for expanding the capabilities of an OTG enabled SmartPhone, Tablet, or other OTG devices, by directly connecting to USB peripherals, such as a USB thumb drive or a USB keyboard and mouse. Add a USB hub to the adapter to create additional ports to connect multiple USB devices. USB OTG technology makes this connection easy, and does not require drivers or software...Plug-n-Play! Connect the adapter to the Micro-B port on an OTG enabled mobile device, and then connect the USB device directly to the USB A port on the adapter for immediate use.

### Features

- Micro USB Male to standard USB "A" Female On-The-Go ( OTG ) adapter
- Plug-n-Play...No Drivers or Software required
- Connect one USB device, or add a multi-port hub for multiple USB device connections
- 6inch length allows for flexible access for attached peripherals

# **Specifications**

OVERVIEW		
UPC Code	037332184375	
INPUT		
Cable Length (ft.)	0.5	
Cable Length (m)	0.2	

### Highlights

- Connect Thumb Drives, Keyboards, etc to OTG Tablets and Phones
- Plug-n-Play...No Software or Drivers Required

### **System Requirements**

 USB OTG enabled Tablet, SmartPhone, or other OTG mobile device

### **Package Includes**

• U052-06N USB OTG Adapter



[	
Cable Length (in.)	6
Cable Length (cm)	15.24
PHYSICAL	
Cable Jacket Rating	VW-1
-	4.5MM
Cable Outer Diameter (OD)	
Color	Black
Material of Construction	PVC
Shipping Dimensions (hwd / cm)	17.78 x 7.62 x 1.27
Shipping Dimensions (hwd / in.)	7.00 x 3.00 x 0.50
Shipping Weight (kg)	0.02
Shipping Weight (lbs.)	0.04
Wire Gauge (AWG)	28/24
ENVIRONMENTAL	
Operating Temperature Range	14 to 140 F (-10 to 60 C)
Storage Temperature Range	-4 to 185 F (-20 to 85 C)
Relative Humidity	10% to 85%, Non-Condensing
CONNECTIONS	
Side A - Connector 1	USB A (FEMALE)
Side B - Connector 1	MICRO-USB B (MALE)
Connector Plating	Nickel
Contact Plating	Gold
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
Technology	USB 2.0 (High Speed); USB
CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies