


# HUBBELL

## Premise Wiring

### LGX Max Series CS Cassette, 36 Port, 18 Duplex CS to 3 MTP, OM3/OM4, Aqua

By Hubbell Premise Wiring  
Catalog # [OCCSM34](#)



Fiber Optic High Density Cassette, LGX Standard Slot Size, 36 CS to 3 MTP, OM3/OM4, Aqua

#### Features

- Utilizes the latest in Compact Duplex Connector Technology
- Fits in a standard LGX Slot
- Provides High fiber density in your current enclosure
- Provides Extreme high density in any size Enclosure
- Easy Access Pull Tab for Quick Disconnect

#### General

Adapter Type	CS Duplex
Application	Interconnect
Catalog Number	OCCSM34
Enclosure Type	LGX
Environmental Conditions	Indoor
Number Of Ports	18
UPC	662620343877

#### Dimensions

Display Size	4.0" x 1.1"
Height	1.1 in

#### Electrical Ratings

Connectivity	Cassette
--------------	----------

#### Conductor Related

Fiber Type	OM3/OM4
Number of Fibers	36

#### Certifications And Compliance

Industry Standard(s)	Telcordia GR-326-CORE
	TIA-568-C.3
	TIA-604-FOCIS

#### Logistics

Carton Quantity	50
-----------------	----

#### Product Assets

[Catalog Page - PREM A7 CatalogPage](#)  
[Catalog Page - PREM G7 CatalogPage](#)  
[Catalogs - Premise Wiring Catalog](#)  
[Literature - LGX Max CS and SN Cassettes](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
PREM-OCCSM34-SPEC-EN | REV 6/2024