# Product data sheet Characteristics

# AP9564

Rack PDU, Basic, 1U, 20A, 120V, (10)5-20; L5-20P





#### Overview

Lead time Usually in Stock	
----------------------------	--



#### Main

Color	Black	
Product or Component Type	PDU	
PDU Type	Basic	
Cord length	12 ft (3.7 m)	
Number of cables	1	
Provided Equipment	Installation guide Rack Mounting brackets	

#### Complementary

Complementary	
Input Voltage	100 V 120 V
Height	1.7 in (4.4 cm)
Width	17.6 in (44.7 cm)
Output Voltage	120 V
Depth	2.2 in (5.7 cm)
Net Weight	5.5 lb(US) (2.5 kg)
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA L5-20P
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Line Rated Current	16 A
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz
Outlet type and quantity	10 NEMA 5-20R

### Environment

cUL Listed[RETURN]UL Listed
23.0000000000113.00000000000 °F (-545 °C)
095 %
010000 ft
-13.0000000000149.0000000000 °F (-2565 °C)
095 %
050000 ft (0.000000000015240.0000000000 m)

# Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304203872
Returnability	No
Country of origin	IN

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7 cm)
Package 1 Width	9.02 in (22.9 cm)
Package 1 Length	18.3 in (46.4 cm)
Package 1 Weight	8.02 lb(US) (3.64 kg)
	, , , , , , , , , , , , , , , , , , , ,

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEEU RoHS Declaration	
Lead free	Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	

### Contractual warranty

Warranty	2 years repair or replace