

AR2480

APC NetShelter SV, Server Rack Enclosure, 42U, Black, 2057H x 800W x 1060D mm with Roof, Castors, Feet, 4 Brackets, Bottom and Side Panels



Overview

| | |
|--------------|--|
| Presentation | Wide Universal IT enclosure with increased cable management options for denser server and networking applications. Includes integrated vertical 1U mounting spaces adjacent the enclosures standard EIA-310 equipment mounting u-spaces that can be removed and replaced with 1U accessories.42U height to easily roll through doorways. |
| Lead time | Usually in Stock |

Main

| | |
|---------------------------|--|
| Product or Component Type | Rack enclosure |
| Number of rack unit | 42U |
| Provided equipment | Baying hardware Doors Key(S) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters 4 x Bolt down brackets Roof Side Panels Unpacking sheet |

Physical

| | |
|----------------------------|---|
| Height | 81.0 in (205.7 cm) |
| Width | 31.5 in (80 cm) |
| Depth | 41.7 in (106 cm) |
| Net Weight | 287.7 lb(US) (130.5 kg) |
| Color | Black |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |
| Maximum Mounting Depth | 30.60 in (77.72 cm) |
| Minimum mounting depth | 6.60 in (16.76 cm) |
| Rack width | 19" |
| Marking | 14 gauge EIA mounting rail 16 gauge front door 18 gauge post 16 gauge rear door 19 gauge roof 18 gauge side panels |
| Permanent permissible load | 1014 Lb(US) (459.94 kg) dynamic 2205 lb(US) (1000.17 kg) static |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Conformance

| | |
|-----------|-----------------------------------|
| Standards | UL 2416 UL 60950-1 EIA-310E |
|-----------|-----------------------------------|

Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 11309 - APC RESALE PRODUCTS |
| GTIN | 731304302070 |
| Returnability | No |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 85.9 in (218.1 cm) |
| Package 1 Width | 37.008 in (94 cm) |
| Package 1 Length | 45.7 in (116 cm) |
| Package 1 Weight | 330.44 lb(US) (149.885 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 5 year repair or replace |
|----------|--------------------------|