



**226**

14/2 UTP Cable  
Audio, Control, and Low Voltage Power

**Construction & Dimensions**

<b>CONSTRUCTION &amp; DIMENSIONS</b>	
<b>CONDUCTOR PARAMETER</b>	
• Number of Conductors	2
• AWG Size	14
• Conductor Stranding	19x27
• Conductor Type	Bare copper
• Nominal DCR	2.7 Ohm/1000ft
• Cabling Lay Length	4 in
• Twists/Foot	3 twist/ft
<b>INSULATION PARAMETER</b>	
• Insulation Type	Thermoplastic
• Insulation Thickness	0.012 in
• Insulation Color Code	1. Black 2.White
<b>SHIELDING PARAMETER</b>	
• Shield Type	None
<b>ELECTRICAL CHARACTERISTICS</b>	

**Overall Construction**

<b>OVERALL CONSTRUCTION PARAMETERS</b>	
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.23 in
Plenum	No
NEC UL Rating	CL3R, FPLR
RoHS Compliant	Yes
Pull Tension	79 lbs
Bend Radius	2.07 in
Cable Weight	42 lbs

**Overall Electrical & Optical Characteristics**

<b>OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS</b>	
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



**226**

14/2 UTP Cable

### Related Products

RELATED PRODUCTS	
Plenum Number	25226B
Aquaseal Direct Burial Number	AQ226
SpeakOn Panel Mount	CN-NL4MP