

Tripp Lite

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

4-Port USB Charging Station, 5V 6A/30W USB Charger Output, UK Version

MODEL NUMBER: U280-004-UK











Charges up to 4 electronic devices at the same time via USB connection. Ideal for quick-charging tablets, cell phones, laptops and other mobile devices.

Description

Whether you're at home or in the office, Tripp Lite's U280-004-UK 4-Port USB Charging Station provides enough ports and power to keep your devices at 100% capacity. No more peering behind furniture to find an available outlet or unplugging one device to charge another. You can charge up to four tablets, cell phones, laptops and other devices at the same time. The U280-004-UK doesn't require a computer, so you can take it anywhere AC power is available.

The U280-004-UK simultaneously provides up to 5V, 1.5A of power per port at maximum capacity. Each individual port supports USB Battery Charging (BC) v1.2 and is capable of delivering up to 5V, 2.4A, which is enough for charging even battery-intensive devices like the Apple® iPad®.

To charge your USB devices, simply connect the 1.2-meter power cord's BS-1363 plug to an AC power outlet, and connect your devices to the available USB ports. The unit protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity. A front LED indicates the unit is turned on and receiving AC power.

Features

Charges Up to 4 Devices at the Same Timeldeal for charging tablets, cell phones, laptops and other devices at home or workConnect devices to unit's USB ports for proficient chargingFunctions anywhere AC power is available—no computer required

Provides Plenty of Juice for ChargingEach individual port supports USB Battery Charging (BC) v1.2 and is capable of delivering up to 5V, 2.4A, enough for charging battery-intensive devices like the Apple iPadSimultaneously provides up to 5V, 1.5A of power per port at maximum capacityProtects against overheating, overcurrent and overcharging

Easy to Use1.2 m power cord with BS-1363 plug connects to AC outletFront LED indicates when unit is turned on and receiving AC power

Specifications

OVERVIEW

Highlights

- 5V, 2.4A per port for charging battery-intensive devices
- 5V, 1.5A per port simultaneously when at maximum capacity
- All four ports support USB Battery Charging (BC) specification v1.2
- Internal dual-voltage power supply with BS-1363 plug
- Protects against overheating, overcurrent and overcharging
- No computer required

Package Includes

- U280-004-UK 4-Port USB Charging Station
- C7 to BS-1363 power cord, 1.2
- Quick Start Guide



Voltage Compatibility (VAC) 10 Input Frequency 50 Input Current 12 USER INTERFACE, ALERTS & CONTRO	C7 to BS-1363 00; 110; 120; 125; 127; 200; 208; 220; 230; 240 50/60Hz 20V (0.8A) / 230V (0.4A) SOLS Blue (Power)		
Plug Type C: Voltage Compatibility (VAC) 10 Input Frequency 50 Input Current 12 USER INTERFACE, ALERTS & CONTRO LED Indicators BI	00; 110; 120; 125; 127; 200; 208; 220; 230; 240 50/60Hz 20V (0.8A) / 230V (0.4A)		
Voltage Compatibility (VAC) 10 Input Frequency 50 Input Current 12 USER INTERFACE, ALERTS & CONTRO LED Indicators BI	00; 110; 120; 125; 127; 200; 208; 220; 230; 240 50/60Hz 20V (0.8A) / 230V (0.4A)		
Input Frequency 50 Input Current 12 USER INTERFACE, ALERTS & CONTRO LED Indicators BI	50/60Hz 20V (0.8A) / 230V (0.4A)		
USER INTERFACE, ALERTS & CONTROLLED Indicators BI	20V (0.8A) / 230V (0.4A)		
USER INTERFACE, ALERTS & CONTROL LED Indicators BI	OLS		
LED Indicators BI			
	Blue (Power)		
CHARGING			
	CHARGING		
Charging Ports / Amps (4	4) 2.4A		
Charging Method US	JSB		
PHYSICAL			
Color	Vhite		
Shipping Dimensions (hwd / cm) 5.4	5.08 x 13.21 x 18.54		
Shipping Dimensions (hwd / in.) 2.	2.00 x 5.20 x 7.30		
Shipping Weight (kg) 0.3	0.39		
Shipping Weight (lbs.) 0.4	0.87		
Unit Dimensions (hwd / cm) 3.	3.1 x 10.6 x 10.1		
Unit Dimensions (hwd / in.) 1.3	.2 x 4.2 x 4.0		
Unit Packaging Type Bo	Зох		
Unit Weight (kg) 0.3	0.21		
Unit Weight (lbs.)	0.46		
ENVIRONMENTAL			
Operating Temperature Range 41	11°F to 95°F / 5°C to 35°C		
Storage Temperature Range -4	4°F to 122°F / -20°C to 50°C		
Relative Humidity 20	20% to 80% RH, Non-Condensing		
Power Consumption (Watts) 38	88W (Operating) 0.26W (Standby)		
CONNECTIONS			
Ports 4			
Side A - Connector 1 BS	3S1363 UK PLUG		
Side B - Connector 1 (4	4) USB A (FEMALE)		



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

FEATURES & SPECIFICATIONS		
Technology	USB	
STANDARDS & COMPLIANCE		
Certifications	Tested to FCC, Reach, RoHs	
Approvals	UL Listed	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies