



AQC422

6 pair 22AWG Ind Shielded CM AQUASEAL, Low Capacitance
Audio and Control Indoor/Outdoor



Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	6
• AWG Size	22
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	17.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC
• Insulation Thickness	0.01 in
• Insulation Color Code	1.Black-Red, 2. Black-White 3. Black-Green 4. Black-Blue 5. Black-Yellow 6. Black-Brown
SHIELDING PARAMETER	-
• Shield Type	Individually Shielded
• Shield Type 2	Aquaseal Water Blocking Tape
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	55 pF/ft
• Nom. Cap. Conductor to Shield	99 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	12
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.51 in
Plenum	No
NEC UL Rating	CM, CL3
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	128 lbs
Bend Radius	4.59 in
Cable Weight	70 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



AQC422

6 pair 22AWG Ind Shielded CM AQUASEAL, Low Capacitance
Audio and Control Indoor/Outdoor

Related Products

RELATED PRODUCTS	-
Plenum Number	D25432
Non Plenum Number	D432
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231